



The ideal submersible pump for clearing tanks and containers, etc. Universally controlled ON/OFF switching height and operation differential via continuously adjustable float switch. The float switch can also be fixed during continuous operation.

E-KTP 3070 Submersible pump

Logistic Information:

Type: E-KTP 3070 Sales unit: 1 pc Art. No.: 41.702.99 20``: 1,920 pcs 40``: 3,920 pcs Ident. No.: 01018 4006825551327 Bar Code: 40"HC: 4,320 pcs Packing: 160 x 220 x 370 mm Weight: 4.4 kg (net) Weight: 4.8 kg (gross)







Features:

- Carrying handle with integrated cable reel
- Continuously adjustable float switch
- Housing made of impact resistant, high quality plastics
- Removal of impurities up to 5 mm in size
- Universal connection 1½" male thread
- High grade 4-coloured cardboard

Technical Data:

230 V ~ 50 Hz - Voltage: - Power: 300 watts - Delivery capacity max.: 7,000 l/h - Delivery height max.: 6 m - Immersion depth max.: 5 m 1 ½" 35 ℃ - Hose connection: - Water temperature max.: - Mains cable length: 10 m - Foreign particle size max.: Ø 5 mm

Logistic Information:

Type: **E-KTP 3070** Tool: Submersible pump Sales unit: 1 pc Art. No.: 41.702.99 20``: 1,920 pcs Ident. No.: 01018 40``: 3,920 pcs Bar Code: 4006825551327 40"HC: 4,320 pcs 160 x 220 x 370 mm Packing: Weight: 4.4 kg (net) Weight: 4.8 kg (gross)

