



# Einhell

**BLUE**

## BG-PM 51 Petrol Lawn Mower

Art.-No.: 34.010.76

The lawn mower, equipped a high quality 4-stroke motor **4.4 kW** (6 HP), warrants a high perfection and reliability, quiet running, economical operation, a lot of power reserve and long service life. The contact free ignition and the automatic decompression offer with the start tension cable easy starting without having to bend down. The wheels equipped with ball bearing let the lawn mower roll along comfortably. The ergonomic design of the handle with soft grip and its 5 fold cutting height adjustment make the unit really service friendly. You can change all 4 wheels with one handle at the same time! Well designed powder-coated sheet steel housing. Sturdy grass collection bag with large volume. Also should be mentioned the problem free transport of the cut grass into the collection bag warranting a high degree of grass intake.

### Features

- Ergonomic guidance bar with soft grip (1)
- 1 cylinder, 4-stroke-motor (2)
- Ball bearing wheels (3)
- Powder-coated sheet steel housing (4)
- Central cutting height adjustment (5)
- Guidance bar 3-settings height adjustable (6)
- Grass collection bin (7)
- Start tension cable integrated at the guide rail (8)
- Space-saving storage
- Full crank shaft
- Recommended for surfaces up to 1,600 m<sup>2</sup>

### Technical Data

- Motor: 1 cylinder, 4-stroke-motor max. **4.4 kW** (6 HP)
- Working idle speed: 2,900 ± 100 min<sup>-1</sup>
- Fuel: gasoline (lead free)
- Tank volume: 2.2 ltrs.
- Motor oil quantity: 0.6 ltrs. (10W30)
- Cover width: 54 cm
- Cutting width: 51 cm
- Collection bag volume: 65 ltrs.
- Central cutting height-adjustment: 5-fold (30-75 mm)
- Noise level L<sub>WA</sub>: 98 dB
- Ignition: contact free (start at the start tension cable)
- Net weight: 39 kg
- Gross weight: 43.7 kg
- Packing dimensions: 900 x 580 x 465 mm
- Bar code: 4006825 549041
- Sales unit: 1 pc



As special accessory available:

**Spare knife**  
Einhell Grey

Art.-No.: 34.055.26  
Bar code: 4006825 541717