

Air Conditioner MKA 2300 E

Art.-No.: 23.603.05

Bar code: 4006825541052

Sales unit: 1pc

Mobile and compact air conditioner, which provides a comfortable indoor climate. Cooling and dehumidifying in one unit. The unit is completely assembled and ready for service after the exhaust hose has been connected. With soft keys and the remote control all operating levels can be set and also the air conditioner can be switched on/off. The thermostat regulation provides a well-balanced indoor climate. This model is suitable for rooms of max. 65 m³ volume.

Features:

- Large control panel (1)
- Air discharge opening lamellas are adjustable mechanically in vertical position (2)
- 4 pcs castors (3)
- Exhaust air hose with adaptor (L max. 150 cm) (4)
- Air suction filter with activated carbon filter (5)
- Remote control (6)
- Condensate return in the cooling operation no condensate box emptying necessary
- Integrated condense water box (approx. 1.21 capacity)
- Constant drainage possible because of condense water hose

Functions:

- LED-Display
- Temperature level: +18° C up to +32° C
- Fan speed: 2-settings
- Operating level section (Mode): Autom., cooling, fan
- Power on-time: 1 to 12 h, Continuous operation



Technical data:

- Free of FCKW (R410A)
- Energy-Efficiency-Class: Α
- EER / COP: 2.81 / -
- Energy consump. when cooling: 404.5 kWh per year - Mains: 230 V ~ 50 Hz
- Cooling capacity: 2,275 watts / 7,800 BTU/h
- Air circulation max.: 300 m³/h
- Exhausted room humidity
- max. (30° C / 80% RH): approx. 24 l a day
- Quantity of coolant: 390 g - Noise level: \leq 54 dB (A)
- Housing dimensions H x W x D: 710 x 310 x 350 mm - Packing dimensions H x W x D: 780 x 510 x 385 mm
- Unit Weight approx.: 23 kg - Weight complete approx.: 25 kg

Characteristics according to active standard EN 14511

LED-Display for:

- Automatic, cooling, fan (7)
- Fan speed (8)
- Condense water box full (9)
- Compressor running (10)
- Timer ON (11)
- Temperature (12)







