



BFO 4200 TI Blue Flame – Gas Heater

Art.-No. 23.323.55

The mobile gas heating appliance needs no chimney connection and can be pursued with customary 5-11 kg of camping gas cylinders. It is planned for the application as an additional stoker in the well ventilated and aired inside area, as well as in the weather-protected undeveloped outskirt area. The device is equipped with a thermostat (area approx. $7^{\circ}C - 32^{\circ}C$) which regulates the achievement of the main distiller (2.0 kW / 4.2 kW) automatically.

Importantly! In Germany the device may be used in well ventilated rooms only with 50mbar interior-gas pressure regulator (2 compression dampings, pressure manometres and thermal protection). **This interior-gas pressure regulator is added to the device serially.**

The generally following regulations are valid for the application of the device:

- Only in well ventilated rooms (durable ventilation and ventilation inevitably) or outside use.
- In leisure vehicles, like caravans and campers, do not use.
- In high rise flats, cellars, bathrooms and bedrooms do not use. It may be used in living rooms not as a long-term heating. The least volume for living rooms amounts to 84 m ³, for other rooms 42 m ³.

Additional regulations in the given countries of destination are to be followed compelling.

Features

- 5-steps thermostat (7℃ 32℃)
- Piezo ignition
- Oxygen deficiency assurance
- Thermoelectric safety pilot
- Pilot light
- "Blue Flame" burner
- Gas bottle space
- Safety gas pressure regulator for indoor (in accordance with EN 12864, DIN 4811 F1-t)
- Gas hose according to EN 1763-1
- 5 pcs guide rollers
- Powder coated sheet steel housing



Technical Data

Nominal rate Σ Qn: 4.2 kW

Gas bottle: Camping 5 kg – 11 kg
Gas type: Propane, Butane or Propane-Butane-Mixtures

Gas consumption G30 (Butane): 305 g/h
Gas consumption G31 (Propane): 300 g/h
Product weight: 10.0 kg

Country	Category	P(mbar)
Code		
AT-DE	I3B/P	50

Gas Injector (1/100 mm)

G30/G31 64/64

Logistic Data

Net weight: 10.0 kgGross weight: 11.0 kg

Packing dimensions: 460 x 320 x 810 mm
Bar code: 4006825 583250

Sales Unit: 1 pc



