

## Dehumidifier LEF 12 M

Art.-No.: 23.691.10

Bar-code: 4006825533323

Sales unit: 1 pc

With the dehumidifier LEF 12 M you could avoid humidity, for example at living-, store- and cellar rooms, and so you would not have wet walls, smelly odours, mould formation and condensation water.

In the machine is a ventilator installed which channels the humid air through an evaporator which cools down the air. Spare humidity gets collected as condensate in a condensate tank and the dehumidified air would be blown out with muted raised temperature.

### Features:

- On/ off switch with humidity-adjustment (40% -80% RH, continuous duty) (1)
- Operating mode display (2)
- Display „condenser full“ (3)
- Air outlet (4)
- Rollers (5)
- Washable dust filter (6)
- Condensate box with float for overflow safety (7)
- **By a continuous operation it's possible to use a hose connection for constant conduction of the condensate**
- **Safety by hose plugging – condensate is redirect in a condensator tank**

### Technical data:

- Operation clamping: 230 V ~ 50 Hz
- Power input: 240 W
- Max. room dimensions: 35 m<sup>3</sup>
- Temperature area: +8°C - +32°C
- Air agitation: 130 m<sup>3</sup>/h
- Dehumidification capacity: at 30°C and 80 % humidity 11 l/day  
at 27°C and 60% humidity 4.5 l/day
- Volume of condensate box approx: 3.8 l
- Cooling fluid: R134a/ 200 g
- Weight: 13.8 kg
- Packing dimensions: 360 x 310 x 570 mm
- Tool dimensions: 310 x 260 x 520 mm
- Tool weight: 12.5 kg

