

Oil Radiator MR 920 LCD

Art.-No.: 23.383.50

Bar code: 4006825510843

Sales unit: 1 pc

In the oil radiator the heat accumulator medium "oil" is used, which heats up very fast. The heat is contained for a long time and after switching off electricity the heat will be transported in the room constantly. The oil radiator is robust and handling it is easy. It is a mobile alternative to the central heating or interseasonal heating. The oil radiator is suitable for warming up the air in closed rooms.

The operating elements are located around a large LCD display at model MR 920 LCD. By pressing the button, the turn-on- and break-time, the desired room temperature and the heating power can be electronically set and can be read at the LCD-display.

Features:

- Mobile housing with 9 fins (1)
- 4 castors (2)
- Grip recess (3)
- Operating panel on the front (4)
- Operating display (5)
- **Simply to read off LCD display (6)**
- Temperature display °F/°C switchable (7)
- **Desired room temperature adjustable (8)**
- **Electronic room temperature regulation (13°-30°C)**
- **2 performance levels (1000/2000 W) (9)**
- **Timer**
- **Turn-on and break-time pre-selectable (1-10 h)**
- Integrated overheating protection
- Stow box for mains cable

Technical data:

- | | |
|------------------------|--------------------|
| - Mains: | 230V ~ 50 Hz |
| - Heating power: | 2000 watts |
| - Protection category: | IP 20 |
| - Protection class: | I |
| - Unit weight: | 11.2 kg |
| - Unit dimensions: | 480 x 240 x 640 mm |
| - Weight: | 12.6 kg |
| - Packing dimensions: | 525 x 160 x 670 mm |

