



# **RT-UD 1825**

### Radial Pull Saw



The radial pull saw RT-UD 1825 is equipped with a powerful motor for cutting and moulding of long and hard materials.

The multipurpose stopper and the precise guidance avoid cants and allow an exact repeat accuracy. Due to this practical pull appliance the saw is ideally suitable for trimming of panels. Special features of the RT-UD 1825 are the saw table made of anodised aluminium, a precise setting of cutting height, twin sawdust extraction and a magnifying glass to support reading of the scales.









### **Features**

- Saw blade pull appliance
- Saw blade protection with extraction hose
- Aluminum guide rail
- Multifunctional angle stop with eccentric clamp
- Saw table made of anodised aluminum
- Saw blade height adjustment
- Saw blade angle adjustment with scale
- Push stick
- Lens for number scale



## **RT-UD 1825**

### Radial Pull Saw



20":

40":

40" HC:

Net weight:

As special accessories available: Art.No.: TCT saw blade Ø 250 x Ø 30 mm, 24 teeth 43.111.10 TCT saw blade Ø 250 x Ø 30 mm, 48 teeth 43.111.11 TCT saw blade Ø 250 x Ø 30 mm, 60 teeth 43.111.13 Under frame 43.106.02

### **Logistic Information**

1 pc

150 pcs

312 pcs

--- pcs

33.0 kg

#### **Technical Data**

Saw blade pull appliance

Type:	RT-UD 1825	Mains:	230 - 240 V ~ 50 Hz
ArtNo.:	43.406.63	Power:	1,800 W (S6 40 %)
Ident-No.:	01017	Idle speed:	4,300 rpm
Bar code:	4006825 541403	Max. cutting height:	73 mm (90°), 50 mm (45°)
Packaging:	830 x 630 x 350 mm	Carbide tipped saw blade:	Ø 250 x Ø 30 x 2,4 mm (48 teeth)
		Swiveling range:	-2°to 47°
Sales unit:	1 pc	Bench size:	660 x 456 mm

Bench size: 660 x 456 mm 220 mm Gauge length:

**Gross weight:** 36.0 kg

