

RT-TC 520 U

Tile Cutting Machine


The radial tile cutting machine can be mounted quickly on the serial type support stand and is therefore suitable for mobile as well as stationary service.

With its unit one can cut wall- and floor tile, split tiles etc. Angle and double mitre cuts are possible and also jolly cuts.

The diamond cutting disc is cooled with the integrated pump for cooling liquids and an almost dust free operation is possible.

The tile cutting machine is equipped with a laser which shows the exact cutting line on the material to be cut. In addition, the laser unit, which is fastened to the machine by a magnetic adapter, can also be removed from the machine and used as a laser leveler when laying flooring materials or similar. The laser unit is therefore equipped with two water levels.








Features


- Removable laser, useable for external work
- RCD plug for machine safety
- Motor guidance from 0°- 45° continuously tiltable
- 4-fold ball-bearing motor guidance
- Sturdy feet
- Aluminium guide rails
- Angle stop with scale for exact cuts
- Working table with antislip rubber mat
- Large water pan
- Diamond cutting disc
- Sturdy machine housing made of sheet steel
- Integrated water pump





RT-TC 520 U

Tile Cutting Machine





Motor guidance from 0°-45° continuously tiltable



Angle stop with scale for exact cuts



Integrated water pan



RCD plug for machine safety



40":

40" HC:

Net weight:

Gross weight:



340 pcs

-- pcs

28.7 kg

31.6 kg

As special accessory available: Turbo diamond cutting disc Ø 200 x Ø 25.4 mm

Ø 200 x Ø 25.4 mm

Art.No.: 43.011.75

Logistic Information

Technical Data

Type:	RT-TC 520 U		Mains:	230 V ~ 50 Hz
ArtNo.:	43.012.71	•	Power:	800 W S1
Ident-No.:	01018	•	Idle speed:	3,000 min ⁻¹
Bar code:	4006825 551914	•	Working table:	570 x 385 mm
Packaging:	890 x 490 x 350 mm	•	Working height:	700 mm
			Cutting depth max.:	90° - 30 mm / 45° - 25 mm
Sales unit:	1 pc	•	Cutting length max.:	520 mm
20":	168 pcs		Mitre cuts:	0 – 45°

Insulation class: IP 54

Diamond disc:

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved. File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\4301271_01018.doc Erstelldatum/create date: 24.07.2008 13:48:00Aktualisiert/up dated: 16.07.2009