

## **25cc PETROL BRUSH CUTTER**

GL-BC 25 S

## **QUICK START GUIDE**

## Easy steps to getting started.

- 1. Ensure all items, including your user guide are removed from the packaging before discarding.
- 2. Assemble petrol brush cutter as per the user guide (Section 6).
- 3. Fuel the petrol brush cutter using unleaded fuel and 2 Stroke oil to a ratio of 40:1. Fill the petrol tank (6) with correct fuel mixture.
- 4. Set the petrol brush cutter down on a hard, level surface.
- 5. Set the choke lever (5) to "".
- 6. Press the fuel pump "primer" (7) 10 times.
- 7. Move the ON/OFF switch (9) to "I".
- 8. Secure the throttle lever (11). To do this, press the throttle lever lock (12).
- 9. Hold the equipment firmly and pull out the starter cable (4) until you feel it start to resist. Then tug sharply on the starter cable (4) 4 times. The equipment should start. Important! Never allow the starter cable (4) to snap back. This may damage the equipment.
- 10. Once the engine has started, move the choke lever (5) immediately to " • "and allow the equipment to warm up for approx. 3 seconds." **Important!** Since the throttle lever (11) is secured, the cutting tool starts to operate when the engine is started. Then release the throttle lever (11) by simply actuating it (the engine then returns to running in idle mode).
- 11. To stop, let go of the throttle lever (11) and wait until the engine has changed to idling speed. Then set the ON/OFF switch (9) to "Stop" or "0".
- 12. IF YOU ARE IN ANY DOUBT PLEASE REFER TO THE DETAILED INSTRUCTIONS WITHIN OUR USER GUIDE.

size: 151 x 196mm



