

## Submersible Pump TMP 501-S Niro (stainless-steel)

## Art.-No.: 41.703.10 bar code: 4006825414899 Sales unit: 4 pcs

Ideal to empty flooded basements, tanks and containers, etc. The installed float switch controls the ON/OFF functions of the pump automatically. With its tremendous capacity of max. 14.000 l/h and a delivery height of max. 8 m this model TMP 501-S in **stainless steel** handles all pumping tasks with ease.

High quality of the material e.g. stainless steel-driving gear, top quality axial face seal, srewed cable locks made of stainless steel warrant an almost maintenance-free and a long service life for semi-professional use. A precise fine-tuning between motor and turbine blade wheel achieves a high degree of effectiveness of various technical data.

**Features:** 

## **Technical data:**

| <ul> <li>Mains:</li> <li>Power:</li> <li>Delivery capacity max.:</li> <li>Delivery height max.:</li> <li>Immersion depth max.:</li> <li>Water temperature:</li> <li>Foreign particles up to:</li> <li>Mains cable:</li> <li>ON function:</li> <li>OFF function:</li> <li>Hose connection:</li> <li>Weight:</li> <li>Packing Dimensions:</li> </ul> | 230 V ~ 50 Hz<br>500 watts<br>14.000 l/h<br>8 m<br>5 m<br>up to 35°C<br>Ø 4 mm<br>10 m H07RN-F (rubber)<br>at approx. 50 cm height<br>at approx. 5 cm<br>1 1/2" female thread<br>8.5 kg<br>335 x 230 x 170 mm | Carrying handle (1)<br>Float switch (2)<br>4-pcs connection kit (3) |
|--|---|---|
| Performance data:  |   |   |
| Delivery height<br>2 m<br>4 m<br>6 m<br>3⁄4" 1"<br>0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0   | Delivery capacity<br>10.000 l/h<br>8.100 l/h<br>6.000 l/h<br>1 <sup>1</sup> /4"<br>2  | ROYAL<br>Finishing<br>TMP 501-S<br>NIRO                             |
| As special accessory availab   | le:   |   |

Drainage hose 10 m / 1"

Art.-No.: 41.737.11 bar code: 4006825414707



File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30\_n0t\Originale\_Englisch\_PA04\4170310\_01010.doccreate date / Erstelldatum 07.05.2001 11:25:00