

Electric Hoist SHZ 125/250

Art.-No.: 22.551.16

Bar code: 4006825515510

Sales unit: 2 pcs

The Professional electric hoist offers you a multiplicity of advantages:

- The control switch is equipped with an **emergency-cut-off button**. This device guarantees a safe cut-off in case of failure of the start switch.
- The control switch is designed in **insulation class II** (safety insulated).
- A forcibly actuated end switch assures that the hoist will safely be cut-off at the upper end (i. e. in case the 2 contacts stick together).
- Improved brake: In case of a defect on the pressure spring (i. e. rupture of the wire) stopping of the load still is assured.
- The brake will be activated in case of power failure in the motor.
- The **non-rotating steel rope** reduces twisting of the loads during the lifting motion.
- The load hook with additional safety latch: This added latch prevents an unintended loosening of the load suspension device.
- The **motor with overload protection** prevents it from overheating.

Features:

- Fastening with 2 double clamps
- Control switch with emergency-cut-off-
- Deflection pulley with payload hook
- 12 m non-rotating (kinking) steel wire Ø 3,05 mm
- Motor with thermal cut-out
- An automatic brake secures the load in any position

Technical data:

Payload: 125 kg without pulley

250 kg with pulley

Lifting height: approx.. 11,5 m without pulley

approx.. 5,7 m with pulley

230 V ~ 50 Hz Mains 500 W S3 20 % Power:

Rope speed: 12 m/min without pulley

6 m/min with pulley

Weight: 11,3 kg

Dimensions: 360 x 220 x 145 mm





Hoist lever arm Art.-No.: 22.553.96 Global SA 1200 Bar code: 4006825221244

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\2255116_01015.doc Erstelldatum / create date: 16.12.2005 10:39:00 Aktualisiert / up dated: 28.03.2008