

## Split-Air Conditioner SKA 2502 C

Art.-No.: 23.651.65

Bar-Code: 4006825514919

Sales unit: 1 pc

One area – Split-Air Conditioner for wall installation with the functions: Cooling and dehumidifying, time programming device for ON/OFF.

**Complete with remote control** and 4 m cooling agent connecting tubes with flexible insulation (max. 15 m possible at professional installation).

Easy installation of the air conditioner with a **cooling capacity of 2,500 W**. Ideal for rooms until approx. 80 m<sup>3</sup>. The unit consists of 2 parts, an outdoor part and one for indoors, in order to allow quick cooling and warrant an optimal noise level.

Fan speed with a maximum speed of 420 m<sup>3</sup>/h.

With the **automatic dehumidification** the units evaporates from its surrounding max. **1,0 l/h** of excess humidity.

**Timer for programme settings, Automatic- and night functions.**

All functions can be set with the **remote control**. Supplied with LCD indicator. Motorized ventilation lamella in the indoor unit.

### Dimensions:

Indoor unit (WxHxD): 710x180x250 mm  
Outdoor unit (WxHxD): 720x260x430 mm

### Weight:

Indoor unit: 11 kg  
Outdoor unit: 27 kg

**Packing dimensions indoor unit:** 750x260x320 mm

**Packing dimensions outdoor unit:** 765x350x500 mm

### Features:

- LED display (1)
- Air escape lamella (2)
- Air suction grid (3)
- Remote control (4)
- Fan (5)
- Pipe connection

### Technical data:

- Coolant:	R407C
- Energy-Efficiency-Class:	D
- EER / COP:	2.62 / -
- Energy consumption at cooling:	480 kWh / Year
- Cooling capacity:	2,500 W / 8,500 BTU/h
- Air throughput:	420 m <sup>3</sup> /h
- Capacity of humidity reduction max:	1.0 l/h
- Mains:	220 - 240 V ~ 50 Hz
- Refrigerant quantity:	500 g for 4 m pipe
- Noise level:	Indoors: ≤ 37 dB (A) Outdoors: ≤ 52 dB (A)

Characteristics according to EN 14511

