



## BT-BC 2 D Battery charger

Art.-No. 10.021.50

220 – 240 V ~ 50 Hz

12 pcs

The BT-BC 2 D is an automatic battery charger controlled by a micro-processor. This means, it's especially to charge maintenance-free batteries as well as for long time charging and for charge maintenance from batteries which are not permanently in use, such as boats, lawn mowers and whatnot. Due to the integrated micro-processor the charging curve has 3 steps. Step one charges the battery with nearly constant current up to approx. 70%, step two with constant voltage up to approx. 90%. Step three keeps the battery voltage constant (IUoU-charging characteristic) and so is the battery always fully loaded. Therefore is the tool also for lead acid battery and gel battery optimally proper. The battery charger is proper for car and bicycle batteries.

BLUE

## **Features**

## **Technical Data**

Mains:

- Charging automatic by a controlled microprocessor LED-display unit on, charging and battery
- fully charged (1)
- Charging leads with sturdy pole clamps (2)
- Electronic overload-, voltage reversal- and short circuit protection
- Power line with european plug

Also proper for gel

batteries!

Rated input current: 0.1 A Rated output current: 2 A 12 V d. c. Rated output voltage: Battery capacity: 3 – 40 Ah Logistic Data Net weight: 0.37 kg Gross weight: 0.5 kg Packing dimensions: 200 x 135 x 60 mm 4006825570748

- Bar code:
- Sales unit:



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved. File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30\_n0t\Originale\_Englisch\_PA04\1002150\_11010.doc Erstelldatum/create date: 23.02.2010 15:00:00Aktualisiert/up dated: 07.04.2011