

The BT-EH 250 electric hoist enables the safe lifting of loads everywhere in the home, garden and workshop, simply by pressing a switch. With its numerous features this cable winch reflects the state of the art. The 12 meter wire cable with a cross-section of 3.2 mm can be used with a guide roller and load hook to lift a maximum load of 250 kg to a height of 6 m. Without the guide roller the maximum load is halved but the lifting height is increased to 11.5 m.

Features

- 12 m wire cable (twist-free, Ø 3.2 mm)
- Guide roller with load hook
- · Operator switch with emergency stop function
- Motor with thermal switch
- · Load hook with safety catch
- · Automatic brake secures the load in every position
- · Automatic limit cut-out
- · Fastening with two double clamps



Technical Data

- Mains supply
- Max. power (S3 | S3%)
- Payload without return pulley
- Payload with return pulley
- Lifting height without return pulley
- Lifting height with return pulley
- Hoisting speed without return pulley
- Hoisting speed with return pulley





Logistic Data

- · Product weight
- · Gross weight single packaging
- Dimensions single packaging
- Pieces per export carton
- Container quantity (20"/40"/40"HC)

9.5 kg 10.7 kg 360 x 145 x 235 mm 2 Pieces 1650 | 2000 | 0

230 V | 50 Hz

500 | 20

125 kg

250 kg

11.5 m

8 m/min

4 m/min

6 m

Illustrations can contain accessories, which are not included in standard extent of delivery Illustration similar (in design), production-wise modifications reserved GS mark belongs to the product itself only, excluded accessory