

Aluminium Green House Concept III/4 mm

Art.-No.: **36.513.42**

Bar code: **4006825564310**

Sales unit: **1 pc**

Due to the fact that the green house (3-panels – single door) was statical proper calculated, anodized aluminium profiles, you don't need any crosswise installing wind bonds. The individual parts which must be installed are limited to a minimum. A patent-registered connecting system, fixed connection points, the pre-assembled window and the pre-assembled door reduce the assembling time significant. High heat insulating, full-page from aluminium profiles bordered 4 mm sheets made of polycarbonate offers an optimal climate in the green house.

It is recommended to embody the green house with one aluminium stand and 4 pcs of ground anchors (are available as accessory) in the ground. Alternatively it can be installed also onto a wall or a concrete stand. The national customary building regulation is to be considered.


The greenhouse is snow load tested with 50 kg/m² and wind load tested with 25 kg/m².

Features:

- High strength, beamless anodized closed aluminium profiles for an optimal reinforcement of geometry
- Patent-registered connecting system
- High quality ridge and corner completion made of powder-coated aluminium – die cast
- Extra high, closed floor sweep
- hexagon socket screw made of stainless steel, rustfree
- Polycarbonate sheets 4 mm, impact and shock resistant, resistant to ball throw, UV-resistant, temperature resisting -25°C to +60°C
- Large single wing door with metal hinges, metal pushers and clip-supported twice bolting device
- 2 pcs at the front side arranged, double sliding windows which can be opened stepless and vertical
- 4 pcs drain gutters with hose preparation

Technical data:

- | | |
|-------------------------------|---------------------|
| - Dimensions L x B: | 230 x 234.4 cm |
| - Eaves height: | 151.5 cm |
| - Ridge height: | 218 cm |
| - Door height (clearance): | 178.3 cm |
| - Door breadth (inner width): | 73.8 cm |
| - Floor space approx.: | 5.39 m ² |
| - Room volume: | 10 m ³ |
| - Panels: | 3 |
| - Thickness sheets: | 4 mm |
| - Net weight: | 49.5 kg |
| - Gross weight: | 71 kg |



Quick & Easy system –
singular assembly technique

As special accessory available:

Aluminium stand

Art.-No.: 36.513.48

Bar code: 4006825564372

Ground anchors BD4 Set

Art.-No.: 36.405.90

Bar code: 4006825514551

Ventilation system

Art.-No.: 36.513.65

Bar code: 4006825574661