

RED

RG-SP 300 RB

Rain Barrel Pump

The practical submersible pump for using rainwater. With an infinitely height-adjustable floating switch so that the switching on/off height and the switching differential can be infinitely adjusted. In addition, the floating switch can be fastened for use in continuous mode. The integrated floating switch and the storage compartment for the extension hose fastened to the pump make this rainwater barrel pump the highlight of the garden season.





Features

- Carrying handle with integrated cable reel
- Continuously adjustable float switch
- High-quality pump housing made of impact-resistant plastics
- Pressure tubes 25, 27 and 30 cm
- Flexible suction tube with stopcock
- Storage compartment for storing the tubes

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved. File: V:\Einhell-AG\TP-BK\2013\TL\T-Sek\01-Sek-allgemein\Azubi\PA04-I-No-Wechsel-Anpassung-08-2013\Originale Englisch-Vorgaenger-Version\4170434_11031.doc Erstelldatum/create date: 26.06.2008 11:31:00Aktualisiert/up dated: 29.08.2013



RG-SP 300 RB

Rain Barrel Pump

Swivelable goose-neck for positioning the garden hose to individual requirements

Stopcock

Rainwater barrel fastener

Hose connection G ¾ (ca. 26.4 mm) male thread



Integrated cable reel


Storage compartment for storing the pressure tubes




Continuously adjustable float

switch

TÜV Styrmind Grop Seprüft





Logistic Information

Technical Data

Typ: RG-SP 300 RB Art.-No.: 41.704.34

Ident-No.: 11031

Bar code: 4006825 549485

Packaging: 250 x 220 x 360 mm

rackaging. 200 x 220 x 3

Sales unit: 4 pcs

20": 1,280 pcs

40": 2,600 pcs **40**" **HC**: 3,410 pcs

Product weight: 5 kg **Gross weight:** 5.55 kg

Voltage: 230 V ~ 50 Hz

Power rating: 300 W

Flow rate max.: 4,600 l/h

Flow rate max.

with extension tubes: 1,750 l/h

Flow height max.: 11 m

Submersion depth max.: 7 m

Hose connection: G ¾ (ca. 26.4 mm) male thread

■ Water temperature max.: 35 ℃

Power cable length: 10 m

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, productionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved.

File: V:\Einhell-AG\TP-BK\2013\TL\T-Sek\01-Sek-allgemein\Azubi\PA04-I-No-Wechsel-Anpassung-08-2013\Originale Englisch-Vorgaenger-Version\4170434 11031.doc