





BG-DP 1340 G Dirt Water Pump

Art.-No. 41.707.40

This pump is suited for tough operation, like overflow, drop shafts and flooded construction sites. The weight of the pump provides an especial secure stand. Through the robust casted pump wheel and the casted / stainless steel housing the pump is especially suited for dirty water. A long service life will be supported, because the double floating ring seal is completely covered by oil. Particles up to Ø 40 mm in size can be taken. An exact fine-tuning between motor and turbine blade wheel achieves performance-effectiveness and above-average performance data.

Features

- Double floating ring seal for a long operating life (1)
- Handle (2), intake housing (5) and motor housing (7) made of stainless steel
- Housing above (3) and housing below (6) made of cast iron
- Hose connection (4) for ca. 50.8 mm (2")
- Float switch (8)
- Pump wheel made of cast iron (9)
- Rope 6 meters (10)

Technical Data

Mains: 230 V ~ 50 Hz
Power: 1,300 W
Delivery capacity max.: 23,000 l/h

Delivery capacity max.: 23,000 i/n
Delivery height max.: 10 m
Immersion depth: 5 m
Water temperature: up to 35 °C

Compression connection: ca. 59.6 mm (G2) female thread

Foreign particle size up to: Ø 40 mmMains cable: 10 m H07RN-F

ON funtion: 70 cmOFF function: 20 cmProduct weight: 22.0 kg

Logistic Information

Net weight: 22.5 kgGross weight: 23.0 kg

Packaging: 300 x 550 x 250 mmBar code: 4006825 577655

Sales unit: 1 po















