



Art.-No. 41.707.42

This pump is suited for tough operation, like overflow, drop shafts and flooded construction sites. The weight of the pump provides an especial secure stand. Through the robust casted pump wheel and the casted / stainless steel housing the pump is especially suited for dirty water. A long service life will be supported, because the double floating ring seal is completely covered by oil. Particles up to \emptyset 40 mm in size can be taken. An exact fine-tuning between motor and turbine blade wheel achieves performance-effectiveness and above-average performance data.

Features

- Double floating ring seal for a long operating life
- Handle, intake housing and motor housing made of stainless steel
- Housing above and housing below made of cast iron
- Hose connction for approx. 50.8 mm (2")
- Float switch
- Pump wheel made of cast iron
- Rope 6 meters

Einhell acus usus

Technical Data

Mains: 230 V ~ 50 Hz
Power: 1,300 W
Delivery capacity max.: 23,000 l/h
Delivery height max.: 10 m
Immersion deepth: 5 m

Water temperature: up to 35°C

Compression connction: approx. 59.6 mm (G2) female thread

Foreign particle size up to: Ø 40 mm
Mains cable: 10 m
ON function: 70 cm
OFF function: 20 cm
Product weight: 22.0 kg

Logistic Data

Net weight: 22.5 kgGross weight: 23.0 kg

Packing dimensions: 300 x 550 x 250 mm
Bar code: 4006825 597882

Sales unit: 1 pc

Performance data











