

Art.-No. 41.709.64

The robust submersible pressure pump is most suitable for delivery of clear water from reservoir, well and shafts. The deep well pump is also able to pump the water up from large depths and because of the multi-stage rotor-system the water can be transfer with much pressure. The integrated motor-thermo protection protects the pump against overloading. The vertical pressure line connection consists of stainless steel and has an approx. 33.3 mm (G1) female thread.

## **Features**

- Robust pressure connection with stainless steel insert
- 2 ring bolts
- Pump housing consist of rust-free stainless steel
- Float switch
- 3 high quality plastic pump wheels
- High quality floating seal



## **Technical Data**

Mains: 230 V ~ 50 Hz
Power: 900 W
Delivery quantity max.: 6,000 l/h
Delivery height max.: 32 m
Immersion depth max.: 8 m
Water temperature max.: 35 °C

Hose connection: approx. 33,3 mm (G1)

Female thread up to 2.5 mm

Contaminant: up to 2
Mains cable: 11 m

Protection class: I
Plastic pump wheels: 3 pcs
Product weight: 8.9 kg

## **Logistic Data**

Net weight: 9.3 kgGross weight: 9.8 kg

Packing dimensions: 245 x 190 x 455 mm
Bar code: 4006825 597752

Sales unit: 1 pc

## Performance data







