

The GC-WW 6538 domestic waterworks enables clear water to be delivered from reservoirs, wells and shafts for use in irrigation systems, washing equipment, toilet flush systems and much more besides. Its robust 650 W motor delivers up to 3,800 liters of water per hour.

Features

- Pressure switch
- Pressure gauge
- Tank 20 liter
- Water filler screw
- Water drain screw

			-
Too	hnin		oto.
			X X
100	hnic	ui 🗩	ulu

Mains supply	220-240 V 50 Hz
Power	650 W
 Max. delivery capacity 	3800 L/h
 Max. delivery height 	36 m
Max. pressure	3.6 bar
 Max. suction height 	8 m
 Max. water temperature 	35 ℃
 Max. activation pressure 	1.5 bar
 Max. cut off pressure 	3 bar
 Suction connection 	33,3 mm (R1 AG)
 Pressure connection 	33,3 mm (R1 AG)
Tank volume	20 L
Power cord	1.4 m H07RN-F







Logistic Data

Product weight	10.38 kg	
 Gross weight single packaging 	12.46 kg	
 Dimensions single packaging 	535 x 300 x 520 mm	
 Pieces per export carton 	1 Pieces	
 Gross weight export carton 	12.46 kg	
 Dimensions export carton 	535 x 300 x 520 mm	
 Container quantity (20"/40"/40"HC) 	320 648 810	

Illustrations can contain accessories, which are not included in standard extent of delivery Illustration similar (in design), production-wise modifications reserved GS mark belongs to the product itself only, excluded accessory