

ANTI-VIBRATIO

CONTROL



RT-RH 26

Rotary Hammer



Technical Data

CE

Mains connection: 220 – 240 V ~ 50 Hz

Power rating: 900 W

■ Speed: 0 – 1,200 min⁻¹

■ Blow rate / strength: 0 – 4,800 min⁻¹ / 2.6 J

Drilling capacity (concrete): 26 mm
 Drill chuck: SDS-plus
 Product weight: 4.7 kg

Logistic Information

Art.-No.: 42.584.35

Bar code: 4006825 565676 **Packaging:** 410 x 130 x 330 mm

 Sales unit:
 3 pcs

 Net weight:
 5.9 kg

 Gross weight:
 6.1 kg

Features

Press control (pressure indicator for optimal contact pressure)

Chiseling (with chisel fixation)Chiseling (without chisel fixation)

- Speed control electronics
- Right/ left rotation
- Rotation stop optionally with or without chisel fixation
- Hammer stop facility
- Additional handle with soft grip
- SDS-Plus-drill chuck
- Metal depth gauge
- Cable clip for fixation of the wound up cable
- Transport and storage case

Special accessory

Art.-No. Description
42.580.90 SDS drill/ chisel set, 12 pcs in alu case

42.580.95 SDS drill set, 5 pcs

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery. Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved.

File: V:\Einhell-AG\TP-BK\2013\TL\T-Sek\01-Sek-allgemein\Azubi\PA04-I-No-Wechsel-Anpassung-08-2013\Originale Englisch-Vorgaenger-Version\PA\2584\S6 11023\doc
1023\doc
1023\d