



TH-SM 2534 Dual

Sliding Mitre Saw Art.-No.: 4300825

Ident-No.: 11024

The TH-SM 2534 Dual drag, crosscut and miter saw has a sawing head which can be tilted infinitely from 0° to +45° to the left and right for high flexibility in setting miters on two sides in just one operation. Equipped with a carbide saw blade in professional quality it is suitable for sawing wood, laminated panels and plastics. The high-quality work table made of die-cast aluminium comes with an exact angle adjustment facility which can be latched in various positions.

Features

- · High-quality HW saw blade
- · For sawing wood, laminated panels and plastics
- · Work table made of die-cast aluminium
- High-quality alu-turntable with exact angle adjustment + latching
- Sawing head infinitely tiltable 0° to +45° to the left and right
- Double tube-mounted drag function for wide workpieces
- · Laser for exact indication of the cut (mains-powered)
- · Integrated cutting depth limit
- · All scales are visible from the working position
- · Workpiece supports on both sides
- · Clamping device for holding the workpiece securely in position

- · Spindle lock for easy blade change
- Transport brace
- · Includes sawdust bag
- · Table insert with scale

Technical Data

Maine accepto	000 \/ 50 -
 Mains supply 	230 V 50 Hz
• Power	2100 W
 Max. power (S6 S6%) 	2350 W 25 %
Idle speed	4000 min^-1
Saw blade	Ø250 x ø30 mm
 Number of saw teeth 	48 Pieces
Mitre cut	-45 ° - +45 °
Swiveling range	-45 ° - +45 °
 Cutting width 90°x 90° 	340 x 75 mm
 Cutting width 90°x 45° 	240 x 75 mm
 Cutting width 45°x 90° 	340 x 42 mm
 Cutting width 45° x 45° 	240 x 42 mm
Diameter of suction adapter	36 mm











Logistic Data

14.8 kg · Product weight · Gross weight single packaging 19.5 kg

· Dimensions single packaging 800 x 575 x 455 mm

· Pieces per export carton 1 Pieces · Gross weight export carton 21 kg

· Dimensions export carton 455 x 80 x 575 mm · Container quantity (20"/40"/40"HC) 130 | 265 | 290

Illustrations can contain accessories, which are not included in standard extent of delivery Illustration similar (in design), production-wise modifications reserved GS mark belongs to the product itself only, excluded accessory