





Table Saw Art.-No.: 4307156

Ident-No.: 11013

With its induction motor, the TE-TS 2231 U bench-type circular saw has an extremely powerful and practically maintenance-free drive which has sufficient power reserves even when heavily loaded. A parallel stop, cross stop and 45° tilting blade on the other hand are features which make this bench-type circular saw an ideal choice for universal use. Thanks to the toolless X-Tend table extension, even long workpieces can be guided safely and without distortion.

Features

- · Powerful, long-lasting induction motor
- · Includes a robust base frame for high stability
- · Integrated chassis and handles ensure mobility
- · Complete with carbide saw blade
- · Blade height adjustment system with ball bearings contributes to safety
- Tilting the blade by up to 45° extends the range of applications
- · Galvanized, robust worktop
- Toolless X-Tend table extension can be swung down
- For universal use thanks to the parallel stop and cross stop
- Connection for dust extractor (100mm) keeps the workplace clean
- Blade guard with suction hose are included in the scope of supply
- · Holders for a push stick and a blade key are directly on the machine
- Push stick is available separately

Technical Data

· Mains supply 230 V | 50 Hz • Max. power (S6 | S6%) 2200 W | 20 % 2800 min^-1 · Idle speed · Saw blade Ø315 x ø30 mm · Number of saw teeth 24 Pieces · Swiveling range of saw blade 45° Max. cutting height at 45° 50 mm • Max. cutting height at 90° 83 mm · Height adjustment continuous 0-83 mm · Diameter of suction adapter 100 mm · Working height 85 cm · Size of working table 800 x 550 mm











Logistic Data

· Table length extension back side

Product weightGross weight single packaging50 kg

• Dimensions single packaging 860 x 570 x 475 mm

Pieces per export cartonGross weight export carton54 kg

• Dimensions export carton 825 x 590 x 435 mm

• Container quantity (20"/40"/40"HC) 96 | 208 | 0



Illustrations can contain accessories, which are not included in standard extent of delivery lilustration similar (in design), production-wise modifications reserved GS mark belongs to the product itself only, excluded accessory

650 x 550 mm