



TH-SS 405 E Scroll Saw

Art.-No. 43.090.40

Precise, complicated work on wood, plastic, aluminium, plexi glass or gypsum are challenges for example in model construction. With the stable parallel arm it is easy to saw accurately. The flexibility of the TH-SS 405 E points itself when working to the millimetre range, sawing perfect round forms and circles out. A blower device removes the dust particles directly in front of the saw blade. The transparent saw blade protection offers optimal security without disturbing the work. For mitre cuts you can adjust the workbench up to 45 degrees.

Features

- Clamping screw for saw blade change (1)
- Saw dust blow device (2)
- Stroke rate electronic (3)
- No-voltage switch
- Connection for dust exhaust (4)
- Adapter for fret saw blades (5)
- Solid saw arm for vibration free cutting

Transmitting height

50 mm / 90° at max. throat depth 10 mm / 45° at max. throat depth

Technical data

Mains: 230 V ~ 50 HzPower: 120 W \$6 30%

80 W S2 20 min Idle speed: 400 – 1.600 rpm

Stroke height: 21 mmSaw blade length: 127 mm

Cutting height max.: 57 mm / 90°, 27 mm / 45°

Throat depth: 406 mm

Table size: 413,5 x 253 mmTable tiltable: 0°bis 45°

Storage space: 440 x 280 mm
Product weight: 12.7 kg

Logistic data

