



Einhell

CLASSIC

TC-BG 200

Bench Grinder
Art.-No.: 4412820
Ident-No.: 11014

The bench grinder TC-BG 200 is a compact, powerful machine for grinding of broaches, deburring and sharpening of blades, shape corrections, etc. in the workshop and the garage. A coarse (K36) and fine (K60) grinding disk is included in delivery. The zero-play ball-bearing shaft enables vibration-free running for sharp grinding results. The robust, heavy compact metal construction and the 4 rubber feet enable comfortable operations. The device has adjustable work supports that can be easily fitted to every grinding job. Adjustable spark reflectors and guard hoods closed laterally ensure safety during grinding.

Features

- 4 rubber feet for safe, low-vibration stand
- Adjustable work supports for different applications
- Compact robust metal construction for a long service life
- Zero-play ball-bearing shaft enables precise operations
- Adjustable spark reflectors for safe operations
- Laterally closed guard hoods for safe operations
- Included coarse and fine grinding disk (K36/K60)
- For massive reparations, shape corrections and polished sections
- For easy reparations as well as resharpening of cuts



Technical Data

- | | |
|----------------------------|------------------------|
| • Mains supply | 230 V 50 Hz |
| • Max. power (S2 S2time) | 400 W 30 min |
| • Idle speed | 2950 min ⁻¹ |
| • Grinding wheels | Ø200 x ø32 x 25 mm |



Logistic Data

- | | |
|--------------------------------------|--------------------|
| • Product weight | 12.9 kg |
| • Gross weight single packaging | 13.25 kg |
| • Dimensions single packaging | 430 x 270 x 290 mm |
| • Pieces per export carton | 1 Pieces |
| • Gross weight export carton | 14 kg |
| • Dimensions export carton | 430 x 270 x 290 mm |
| • Container quantity (20"/40"/40"HC) | 850 1700 2000 |

Illustrations can contain accessories, which are not included in standard extent of delivery
Illustration similar (in design), production-wise modifications reserved
GS mark belongs to the product itself only, excluded accessory