



BT-BC 22 E

Battery Charger

Item No.: 1003120

Ident No.: 11041

Bar Code: 4006825101461

The BT-BC 22 E is a powerful, automatic 12 V electronic battery charger with charging current switch for normal- and quick charging for starting aid. Thereby, the inbuilt ampere meter allows the quick reading of the current charging rate. When the switch is set on "A", the charging voltage is limited to a maximum of 14.1 V (WU-charging curve) due to its charging electronics. Therefore an overload of the connected battery is excluded, and no special control of the charging procedure is required any longer. So the battery charger is especially suitable for modern, maintenance-free batteries, and optimal for the preserving charging of sparely used batteries. The strong terminal clamps grant an optimal contact to the battery terminals.

Features

- All-insulated construction
- Overload- and fals poling- and short-circuit protection
- Charging electronic
- Sheet steel housing
- Carrying handle
- Switch for automatic and normal charging
- Switch for normal and rapid charging
- Built-in ammeter
- Mains cable with europe plug
- Charging leads with sturdy pole clamps

Technical Data

- Charging voltage

- Suitable for batteries (from min. Ah to 5-300 Ah

max. Ah):

- Charging current Min. (arith./eff.) - Max. 4,6 / 7 - 14,5 / 22 A

(arith./eff.) on 12 V d.c.

- Mains supply 230 V | 50 Hz

Logistic Data

- Product weight 6.8 kg - Gross weight single packaging 7.5 kg 2 Pieces - Pieces per export carton - Gross weight export carton 15.5 kg

330 x 255 x 170 mm - Dimensions single packaging 540 x 340 x 190 mm - Dimensions export carton

- Container quantity (20"/40"/40"HC) 1650 | 0 | 0



















