

Ident No.: 11014

Bar Code: 4006825603491

The BT-BO 16/1 A LED SP jumper cable provides good service for jump starting petrol engines. The 4 pole clamps are fully insulated and equipped with LED lighting. The conductive material is made of 19.4 mm² aluminium (= 16 mm² copper cable). The safe jump starting function is guaranteed by the integrated surge protection which protects against harmful voltage peaks. Delivered in a practical carrying bag, the jumper cable is compliant with DIN 72553-16.

Features

- Jumper cables tested according to DIN 72553-16
- 4 all-insulated pole-pliers
- Conductive material made of 19.4 mm² alu (= 16 mm² copper cable)
- Pliers with LED-lighting
- Surge protection against harmful voltage peaks while jumpstarting
- Incl. carrying bag

Technical Data

- For petrol engines up to max.
- Cable length

- Testing current

- Cable cross section
- 3 m 19.4 mm² 220 A

2500 cm³

Logistic Data

- Product weight	1.2 kg
- Gross weight single packaging	1.25 kg
- Pieces per export carton	6 Pieces
- Gross weight export carton	8 kg
- Dimensions single packaging	280 x 280 x 60 mm
- Dimensions export carton	560 x 280 x 175 mm
- Container quantity (20"/40"/40"HC)	6000 12462 14652





