





BT-BO 25/1 A LED SP

Booster Cable

Item No.: 2030365

Ident No.: 11014

Bar Code: 4006825603514

The BT-BO 25/1 A LED SP jumper cable provides good service for jump starting petrol or diesel engines. The 4 pole clamps are fully insulated and equipped with LED lighting. The conductive material is made of 31.4 mm² aluminium (= 25 mm² copper cable). The safe jump starting function is guaranteed by the integrated surge protection which protects against harmful voltage peaks. Delivered in a practical carrying bag, the jumper cable is compliant with DIN 72553-25.

Features

- Jumper cables tested according to DIN 72553-25
- 4 all-insulated pole-pliers
- Conductive material made of 31.4 mm² alu (= 25 mm² copper cable)
- Pliers with LED-lighting
- Surge protection against harmful voltage peaks while jumpstarting
- Incl. carrying bag



5500 cm³ - For petrol engines up to max. 3000 cm³ - For diesel engines up to max. - Cable length $3.5 \, m$ - Cable cross section 31.4 mm² - Testing current 350 A



- Product weight 1.45 kg - Gross weight single packaging 1.79 kg - Pieces per export carton 6 Pieces - Gross weight export carton 9.5 kg

320 x 320 x 60 mm - Dimensions single packaging - Dimensions export carton 640 x 320 x 185 mm - Container quantity (20"/40"/40"HC) 4344 | 9000 | 10578







