

Bar Code: 4006825596380

The BT-BO 25/1 A SP jumper cable provides very good service for jump starting petrol or diesel engines. It is equipped with 4 fully insulated pole clamps. The conductive material is made of 31.4 mm² aluminium (= 25 mm² copper cable). The safe jump starting function is guaranteed by the integrated surge protection which protects against harmful voltage peaks. Delivered in a practical carrying bag, the jumper cable is compliant with DIN 72553-25.

Features

- Jumper cables tested according to DIN 72553-25
- 4 all-insulated pole-pliers
- Conductive material made of 31.4 mm² alu (= 25 mm² copper cable)
- Surge protection against harmful voltage peaks while jumpstarting
- Incl. carrying bag

Technical Data

- For petrol engines up to max.
- For diesel engines up to max.
- Cable length
- Cable cross section - Testing current

3000 cm³ 350 cm 31.4 mm²

5500 cm³

Logistic Data

- Product weight	1.95 kg
- Gross weight single packaging	1.95 kg
- Pieces per export carton	6 Pieces
- Gross weight export carton	12 kg

- Dimensions single packaging
- Dimensions export carton
- Container quantity (20"/40"/40"HC)

350 A

320 x 320 x 60 mm

640 x 320 x 190 mm

4230 | 8772 | 10308



