

Features

- Number scale with loupe
- Push stick with clamp
- Cross fence with angle scale
- Additional tilt protection
- Table broadening and elongation made of powder coated sheet steel
- Anodised table surface for better antifriction properties
- Powder coated housing
- Saw blade protection with dust extraction device
- Laser
- Parallel stop with aluminium guide
- Saw blade angle adjustment
- Saw blade height adjustment
- 1 additional saw blade Ø 250 x Ø 30 x 3 mm, 48 teeth
- Waste bag (textile) for wood residues

Technical Data

| | |
|------------------------------------|-------------------|
| - Idle speed | 6500 min-1 |
| - Number of saw teeth | 24 / 48 Pieces |
| - Swiveling range of saw blade | 45 ° |
| - Max. cutting height at 45° | 54 mm |
| - Max. cutting height at 90° | 72 mm |
| - Height adjustment continuous | 0-72 mm |
| - Diameter of suction adapter | 36 mm |
| - Working height | 895 mm |
| - Mains supply | 230-240 V 50 Hz |
| - Max. power (S6 S6%) | 1700 W 40 % |
| - Saw blade | Ø250 x ø30 mm |
| - Size of working table | 610 x 445 mm |
| - Table broadening left | 608 x 250 mm |
| - Table broadening right | 608 x 250 mm |
| - Table length extension back side | 435 x 320 mm |

Logistic Data

| | |
|--------------------------------------|--------------------|
| - Product weight | 25.56 kg |
| - Gross weight single packaging | 29.36 kg |
| - Pieces per export carton | 1 Pieces |
| - Gross weight export carton | 29.36 kg |
| - Dimensions single packaging | 700 x 580 x 355 mm |
| - Dimensions export carton | 700 x 580 x 355 mm |
| - Container quantity (20"/40"/40"HC) | 180 360 420 |

