

Electric Hoist YPL 250

Art.-No.: **22.551.15**

Bar-Code: 4006825504538

Sales Unit: 2 pcs

The Zgonc electric hoist offers you a multiplicity of advantages:

The start button is equipped with an **emergency-cut-off button**. This device guarantees a safe cut-off in case of failure of the start switch.

- The start button is designed in **insulation class II** (safety insulated).
- A **forcibly actuated end switch** assures that the hoist will safely be cut-off at the upper end (i. e. in case the 2 contacts stick together).
- **Improved brake:** In case of a defect on the pressure spring (i. e. rupture of the wire) stopping of the load still is assured.
- The brake will be activated in case of power failure in the motor.
- The **non-rotating steel rope** reduces twisting of the loads during the lifting motion.
- The load hook with **additional safety latch**: This added latch prevents an unintended loosening of the load suspension device.
- The **motor with overload protection** prevents it from overheating.

Features:

- Fastening with 2 double clamps
- Start button with emergency button
- Deflection pulley with payload hook
- 12 m non-rotating (kinking) steel wire
Ø 3,18 mm
- Motor with thermal cut-out
- An automatic brake secures the load in any position

Technical data:

- Payload: 125 kg without pulley
250 kg with pulley
- Lifting height: approx.. 11,5 m without pulley
approx.. 5,7 m with pulley
- Mains 230 V ~ 50 Hz
- Power: 550 W S3 25 %
- Rope speed: 10 m/min without pulley
5 m/min with pulley
- Weight: 11,5 kg
- Dimensions : 350 x 220 x 140 mm



As special accessory available:

Hoist lever arm
Global SA 1200

Art.-No.: **22.553.96**
Bar-Code: 4006825221244

Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved

File: G:\Webshop\T-Produktbeschreibung\60\Originale_Englisch_PA04\2255115_01025.doc

Erstelldatum / create date: 19.05.2005 1:55

Aktualisiert / up dated: 02.06.2005