



Einhell®

Heating Generator LE-HGG 110 EX

Art.-No.: 23.301.21

bar code: 4006825504323

sales unit: 1 pc

Due to the high efficiency design and construction of the unit it could be kept small and handy with a high output. The normal connection is to a 5 resp. 11 kg propane/butane gas bottle. The integrated Piezo ignition as well as the thermal cut-out against over heating cut off the gas and warrant a safe operation.) **Gas hose and pressure reducer are not supplied for sales in following countries:** BG, BE, CH, CZ, DK, ES, FI, GB, HU, IE, IT, LU, NL, NO, PT, SE

Unit is not to be used for professional service!

For professional service to be used only in connection with gas hose rupture device according DIN 30693 (special accessory)

Features:

- ON/OFF-switch for fan
- gas valve button
- heating reflector made of galvanized sheet steel (1)
- housing made of varnished sheet steel (2)
- carrying handle (3)
- Piezo ignition (4)
- Back-fire safety device
- Piezo electrical flame safety
- Solenoid valve
- Mains cable (5)

Technical data:

- | | |
|-------------------------------|------------------------|
| - Mains: | 230 V ~ 50 Hz, 38 W |
| - Nominal heat load: | 11:2 KW |
| - Nominal air volume: | 500 m ³ /h |
| - Nominal gas consumption: | 815 g/h liquid gas P/B |
| - Operating pressure: | 300 mbar |
| - Type of gas propane/butane: | class I.3 |
| - Weight: | 5:7 kg |
| - Packing dimensions: | 400 x 230 x 310 mm |



As special accessory available:

Gas hose rupture device

Art.-No.: 33.912.30

Bar code: 4006825338348