

Heating Generator HGG 300 Niro

Art.-No.: 23.309.10

Bar code: 4006825237078

Sales unit: 1 pc

Due to the high efficiency design and construction of the unit it could be kept small and handy with a high output. The normal connection is to a 5 resp. 11 kg propane gas bottle. The integrated Piezo ignition as well as the thermal cut-out against over heating cut off the gas and warrant a safe operation.) A gas hose and the pressure reducer with integrated gas hose rupture device is supplied as standard equipment.

Unit can be used for professional service! (Attention! For professional service to be used only in connection with the supplied pressure reducer or gas hose rupture device according DIN 30693!)

Features:

- ON/OFF-switch for fan (1)
- gas valve button
- heating reflector made of galvanized sheet steel (2)
- housing made of stainless steel (3)
- carrying handle (4)
- Piezo ignition
- Back-fire safety device
- Piezo electrical flame safety
- Solenoid valve
- Mains cable

Technical data:

- | | |
|----------------------------|------------------------|
| - Mains: | 230 V ~ 50 Hz, 38 W |
| - Nominal heat load: | 30 KW |
| - Nominal air volume: | 500 m ³ /h |
| - Nominal gas consumption: | 2150 g/h liquid gas P |
| - Operating pressure: | 1,5 bar |
| - Type of gas: | propane acc. DIN 51622 |
| - Weight: | 6,2 kg |
| - Packing dimensions: | 460 x 235 x 325 mm |

