

Outdoors: $\leq 51 \text{ dB}$ (A)

Split-Air Conditioner SKA 3501 C + H

Art.-No.: 23.652.10 Bar-Code: 4006825509120 Sales unit: 1 pc

Air conditioner for cooling and heating for wall installation. Automatic dehumidifying of air in a room

Complete with remote controlled transmitter and 4 m cooling agent connecting tubes with flexible insulation (max. 15 m possible at professional installation).

Time programming device for ON/OFF.

Easy installation of the air conditioner with a cooling capacity of 3.200 watts/ 11.000 BTU and a heating capacity of 3.800 watts/ 13.000 BTU/h. Ideal for large rooms until approx. 110 m³. The unit consists of 2 parts, an outdoor part and one for indoors, in order to allow quick cooling and warrant an optimal noise level. Due to the possibility of heating operation, the air conditioner can additionally also be used as "interseasonal heating".

Fan speed with a maximum speed of 500 m³/h.

With the **automatic dehumidification** the units evaporates from its surrounding **1.2 l/h** excess humidity.

Timer for programme settings, Automatic- and night functions.

All functions can be set with the **remote controlled transmitter.** Supplied with LCD indicator. Motorized ventilation lamella in the indoor unit.

Dimensions:		Т	echnical data:	
Indoor unit (WxDxH):	890 x 180 x 300 mm	-	Free of FCKW (R407C)	
Outdoor unit (WxDxH):	760 x 540 x 260 mm	-	Energy-Efficiency-Class:	С
		-	EER / COP:	2,83 / 3,23
Weight:		-	Energy consumption when cooling:	667,5 kWh per year
Indoor unit:	10,5 kg	-	Cooling capacity:	3.200 watts / 11.000 BTU/h
Outdoor unit:	38 kg	-	Heating capacity:	3.800 watts / 13.000 BTU/h
Weight complete:	48,5 kg	-	Air throughput:	500 m³/h
Packing dimensions complete:	appr. 960x390x865mm	-	Capacity of humidity reduction:	1,2 l/h
		-	Mains:	230 V ~ 50 Hz
Features:		-	Rated power during cooling:	1.300 watts
- Air suction grid (1)		-	Power during heating:	1.350 watts
- Air escape plate fin (2)		-	Refrigerant quantity:	1080 g for 4 m pipe
- LED-display (3)		-	Noise level:	Indoors: \leq 41 dB (A)

- LED-display (3)
- Remote control (4)
- Fan (5)
- Pipe connection



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, productionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved File: \\100.0.1.101\office\Webshop\T-Produktbeschreibung\60\Originale_Englisch_PA04\2365210_01014.doc Erstelldatum / create date: 17.01.2005 13:41 Aktualisiert / up dated: 04.05.2005