

Split-Air Conditioner SKA 2501 EO C + H

- Remote control (4) - Pipe connection (5)

Art.-No.: 23.657.11 Bar-Code: 4006825529272 Sales unit: 1 pc

Air conditioner for cooling and heating with a cooling capacity of 2.500 watts and a heating capacity of 2.850 watts - for wall installation. Automatic dehumidifying of air in a room.

Complete with remote controlled transmitter, 4 m cooling agent connecting tubes (made of copper resp. coated by stainless steel reinforcement) and flexible insulation protection hose, tube ends equipped with quick release (fig. A) Time programming device for ON/OFF.

The air conditioner consists of two parts, an outdoor part and one for indoors. This allows a quick cooling and warrant an optimal noise level. Due to the quick catches installed at the ends of the cooling agent tubes, the connection of the cooling agent tubes between outdoor and indoor unit is extremely simple and easy to install for everyone. The max. cooling agent tube length is 4 m. The air conditioner is ideal for large rooms until approx. 80 m³.

Due to the possibility of heating operation, the air conditioner can additionally also be used as "interseasonal heating".

3 setting of fan speed with a maximum speed of 420 m³/h. With the automatic dehumidification the units evaporates from its surrounding 1,0 l/h excess humidity. Timer for programme settings, Automatic- and night functions. All functions can be set with the remote controlled transmitter. Motorized ventilation lamella in the indoor unit.

		T		
Dimensions:		T	echnical data:	
Indoor unit (WxDxH):	800 x 160 x 250 mm	-	Free of FCKW (R407C)	
Outdoor unit (WxDxH):	830 x 255 x 545 mm	-	Energy-Efficiency-Class:	В
		-	EER / COP:	3.01 / 3.43
Weight:		-	Energy consumption when cooling:	415 kWh per year
Indoor unit:	8 kg	-	Cooling capacity:	2.500 watts
Outdoor unit:	32 kg	-	Heating capacity:	2.850 watts
Weight total gross:	47 kg	-	Air throughput:	420 m³/h
Packing dimensions compl.:	appr. 935x350x835 mm	-	Capacity of humidity reduction:	1.0 l/h
(WxDxH):		-	Mains:	230 V ~ 50 Hz
		-	Refrigerant quantity:	approx. 800g for 4 m of tube
Features:	0	-	Noise level:	Indoors: \leq 38 dB (A)
- LCD-display (1)				Outdoors: \leq 53 dB (A)
- Air suction grid (2)		C	haracteristics according to EN 14511	
- Air escape lamella (3)			C	

A



Abbildungen können nicht im Serien-Lieferumfang enthaltenes Zubehör darstellen / Illustrations can contain accessories, which are not included in standard extent of delivery.

Abbildungen ähnlich, produktionsbedingte Abweichung vorbehalten / Illustration similar (in design), production-wise modifications reserved File: S:\shared-pool\Product-Documentation\T-Produktbeschreibung\30_n0t\Originale_Englisch_PA04\2365711_01016.doc Erstelldatum / create date: 14/03/2006 08:38:00 Aktualisiert / up dated: 05/09/2006