

Scroll Saw DKS 405/1 E

Art.-No.: 43.090.10

bar code: 4006825501216

sales unit: 1 pc

You can work with the Scroll Saw precise and complicated on wood, plastic, metal, plexi glass and gypsum. Using especially in model construction and handcraft work.

With the stable parallel arm is it easy to saw accurately straightforward..

The flexibility of the DKS 405/1 E points itself when working to the milimetre range, sawing perfect round forms and circles out. A blower device removes the dust particle directly from the working piece. The transparent saw blade protection offers optimal security without disturbing the work. For mitre cuts you can adjust the workbench over up to 45 degrees.

Technical data:

Mains: $230 \text{ V} \sim 50 \text{ Hz}$ - Cutting height max.: $57 \text{ mm/}90^{\circ}$, $27 \text{ mm/}45^{\circ}$

Power: 120 watts S2 5 min. Throat depth: 406 mm Idle stroke speed: n₀: 400-1600 min⁻¹ Table size: 410 x 253 mm Height of stroke: 21mm Table tiltable: 0° to 45° Length of saw blade: 127 mm 410 x 245 mm Space required:


Weight: 12 kgPacking dimensions: 630 x 280 x 330 mm

Transmitting heigth:

 $50 \text{ mm} / 90^{\circ}$ at max. throat depth $10 \text{ mm} / 45^{\circ}$ at max. throat depth

Features:

- Sawdust blower facility (1)
- Stroke rate electronic (2)
- no-voltage releasing magnet (3)
- dust extraction device (4)
- adapter for leave saw blades (5)



As special accessory available:

Spare saw blade Art.-No.: 45.062.00 (Set 5 pcs) bar code: 4006825453928



up dated / aktualisiert: 23.02.2005