



Fan Heated Tower

HT 2000

Item No.: 2338823

Ident No.: 11016

Bar Code: 4006825621358

The HT 2000 tower heater has a PTC ceramic heating element with three power settings, namely a blower setting, 1200 W and 2000 W, for setting it to the desired feel good temperature. The HT 2000 also features a selectable oscillation function. For ease of use the HT 2000 has an On/Off switch to enable it to be activated and an IR remote control for adjusting the settings. The function display can be read on the LED display. The switch-off time can be set in advance to between half-an-hour and 7.5 hours. The safety cut-out ensures that the HT 2000 switches off if it tips over or overheats. For easy transportation there is an integrated trough handle on the housing.

This product is only suitable for well insulated spaces or occasional use.

Features & Benefits

- PTC ceramic heating element
- 3 settings (Blower/1200 W/2000 W)
- Oscillation function
- Programmable switch-off (0.5 7.5 hours)
- Functions displayed using LED panel
- Infrared remote control
- Safety cut-out if the heater tips over
- Safety cut-out if the heater overheats
- On/Off switch
- Built-in recessed handle
- Air filter

Technical Data

- Mains Supply 220-240 V | 50 Hz

- Heating output power 2000 W

Protection class (against electric shock)II
Unit Dimensions
21.5 x 21.5 x 78 cm

Logistic Data

- Product weight 3.93 kg- Gross weight single packaging 5.12 kg

- Dimensions single packaging 275 x 147 x 835 mm

- Pieces per export carton- Gross weight export carton5 kg

Dimensions export carton
145 x 275 x 835 mm
Container quantity (20"/40"/40"HC)
840 | 1700 | 1900

















