



**Booster Cable** 

BT-BO 25/1 A

Item No.: 2030345

Ident No.: 11046

Bar Code: 4006825561555

The BT-BO 25/1 A jumper cable provides very good service to even the inexperienced when helping out with bridging or jump starting petrol or diesel engines. It is equipped with 4 fully insulated pole clamps. The conductive material is made of 31.4 mm<sup>2</sup> aluminium (= 25 mm<sup>2</sup> copper cable). Delivered in a practical carrying bag, the jumper cable is compliant with DIN 72553-25.

## **Features & Benefits**

- Jumper cables tested according to DIN 72553-25
- 4 all-insulated pole-pliers
- Conductive material made of 31,4 mm<sup>2</sup> alu (= 25 mm<sup>2</sup> copper cable)
- Incl. carrying bag

## **Technical Data**

5500 cm<sup>3</sup> - For petrol engines up to max. - For diesel engines up to max. 3000 cm<sup>3</sup> - Cable length 3.5 m - Cable cross section 31.4 mm<sup>2</sup> - Testing current 350 A



## **Logistic Data**

- Product weight 1.81 kg - Gross weight single packaging 1.9 kg

- Dimensions single packaging 320 x 320 x 65 mm

- Pieces per export carton 6 Pieces - Gross weight export carton 11.5 kg

640 x 320 x 190 mm - Dimensions export carton - Container quantity (20"/40"/40"HC) 4230 | 8772 | 10308





