



**All Purpose Saw** 

## **TE-AP 950 E**

ltem No.: 4326180

Ident No.: 11017

Bar Code: 4006825632699

The Einhell TE-AP 950 E universal saw makes light work of sawing jobs in a wide variety of materials thanks to its 950 W power rating and electronic stroke speed control for adjusting the tool to the particular material and application. The soleplate needs no tools for adjustment and therefore enables the blade to be used to optimum effect. The saw blade can be changed quickly without the need for any tools. For comfortable and safe operation there is a large soft grip area to ensure that the universal saw always lies comfortably and securely in the hand. The ergonomic and slimline design makes it easy to handle. A KWB quality saw blade for wood is included.

## **Features & Benefits**

- Electronic stroke speed control for adjusting to application
- Soleplate adjustable without tools for optimum blade use
- Blade change without tools
- Large soft grip area for comfortable and safe operation
- Ergonomic, slim design for easy handling
- Complete with KWB quality saw blade for wood

## **Technical Data**

| - Mains supply           | 220-240 V   50 Hz |
|--------------------------|-------------------|
| - Power                  | 950 W             |
| - Number of strokes      | 0 - 2800 min^-1   |
| - Stroke height          | 28 mm             |
| - Cutting depth in wood  | 200 mm            |
| - Cutting depth in steel | 20 mm             |
|                          |                   |

## Logistic Data

| - Product weight                                  | 3.39 kg            |
|---|--------------------|
| <ul> <li>Gross weight single packaging</li> </ul> | 3.73 kg            |
| - Dimensions single packaging                     | 500 x 95 x 200 mm  |
| - Pieces per export carton                        | 4 Pieces           |
| <ul> <li>Gross weight export carton</li> </ul>    | 16.01 kg           |
| - Dimensions export carton                        | 55 x 38 x 24 mm    |
| - Container quantity (20"/40"/40"HC)              | 2240   4630   5440 |
|   |                    |







