



Einhell

CLASSIC

Hand Lever Winch

TC-LW 1000

Item No.: 2260140

Ident No.: 11018

Bar Code: 4006825643237

The Einhell TC-LW 1000 hand lever winch is suitable for pulling and tensioning loads with a maximum tensile load of 1000 kg and a maximum useable distance of 1.2 meters. The product is supplied with a 2.2 meter twist-free wire cable (Ø 4.8 mm) and a guide roller with load hook which has a retention latch. The retention latch prevents the load from being unhooked accidentally. An automatic brake secures the load in every position. There is a safety clip to prevent a complete unrolling of the cable. The winch comes with a tensioning spring for releasing the retaining catch easily. The hand lever winch is not suitable for lifting and lowering loads.

Features & Benefits

- 2.2 m twist-free wire cable (Ø 4.8 mm)
- Incl. guide roller with load hook & retention latch
- Retention latch prevents the load being unhooked accidentally
- Suitable for pulling and tensioning loads
- Not suitable for lifting and lowering loads
- An automatic brake secures the load in every position
- Tensioning spring for releasing the retaining catch easily
- The max. payload with guide roller is 1000kg
- Safety clip prevents complete unrolling of the cable




Technical Data

- | | |
|----------------------------------|---------|
| - Max. useable distance | 1.2 m |
| - Steel cable diameter | 4.8 mm |
| - Steel cable length | 2.2 m |
| - Automatic brake | yes |
| - Max. payload with guide roller | 1000 kg |

Logistic Data

- | | |
|--------------------------------------|--------------------|
| - Product weight (kg) | 2.75 |
| - Gross weight (kg) | 2.93 |
| - Dimensions single packaging | 108 x 75 x 560 mm |
| - Pieces per export carton | 6 Pieces |
| - Gross weight of export carton | 17 kg |
| - Dimensions export carton | 590 x 240 x 235 mm |
| - Container quantity (20"/40"/40"HC) | 3840 7680 |



SAFETY HOOK



AUTOMATIC STOP




GUIDEROLLER




TENSIONING SPRING




SOFTGRIP



max. 1000 kg



USABLE DISTANCE
max. 1.2 m



CABLE
4.8 mm