



Einhell

EXPERT PLUS



Cordless Light

TE-CL 18 Li-Solo

Item No.: 4514110

Ident No.: 11013

Bar Code: 4006825600032

The TE-CL 18 Li – Solo rechargeable lamp provides plenty of light when you are working in the dark or in areas with poor lighting. Three high-power LEDs provide extra-bright light. The lamp has very low power consumption and continues to provide lighting for an extremely long time (up to 33 hours).

Features & Benefits


- Member of the Power X-Change family
- Three high-power LEDs provide extra-bright light
- Low power consumption therefore up to 33h light on time
- Adjustable diffusion angle (concentrated or wide-angle lighting)
- 135° degree continuous lamphead adjustment
- Rugged housing with carry handle and soft grip
- Supplied without battery and charger (available separately)

Technical Data

- Number of LED 3 Pieces
- Luminous flux 270 lm

Logistic Data

- Product weight 0.17
- Gross weight single packaging 0.21
- Dimensions single packaging 90 x 50 x 180 mm
- Pieces per export carton 60 Pieces
- Gross weight export carton 14.7 kg
- Dimensions export carton 580 x 305 x 290 mm
- Container quantity (20"/40"/40"HC) 36000 | 72960 | 72960



Available as special accessories



18V 30min Power X-Change
Charger
Item No.: 4512011
Bar Code: 4006825587029
Einhell Accessory



18V 5,2 Ah P-X-C Plus
Battery
Item No.: 4511437
Bar Code: 4006825616606
Einhell Accessory



Power-X-Boostcharger 6 A
Charger
Item No.: 4512064
Bar Code: 4006825629019
Einhell Accessory



Power-X-Twincharger 3 A
Charger
Item No.: 4512069
Bar Code: 4006825629729
Einhell Accessory



18V 4,0Ah PXC Starter Kit
PXC-Starter-Kit
Item No.: 4512042
Bar Code: 4006825613704
Einhell Accessory



18V 2,0 Ah Power-X-Change
Battery
Item No.: 4511395
Bar Code: 4006825610369
Einhell Accessory



18V 4,0 Ah Power-X-Change
Battery
Item No.: 4511396
Bar Code: 4006825610376
Einhell Accessory



18V 3,0Ah PXC Starter Kit
PXC-Starter-Kit
Item No.: 4512041
Bar Code: 4006825613698
Einhell Accessory

Battery-Running-Times

running time (in h)

Usage	shining	
Unit of measure	h	
with 1.5 Ah PXC	8	<div style="width: 8%; height: 10px; background-color: red;"></div>
with 2 Ah PXC	10	<div style="width: 10%; height: 10px; background-color: red;"></div>
with 2.5 Ah PXC	12	<div style="width: 12%; height: 10px; background-color: red;"></div>
with 2.6 Ah PXC+	13	<div style="width: 13%; height: 10px; background-color: red;"></div>
with 3 Ah PXC	16	<div style="width: 16%; height: 10px; background-color: red;"></div>
with 3.0 Ah PXC+	16	<div style="width: 16%; height: 10px; background-color: red;"></div>
with 4 Ah PXC	22	<div style="width: 22%; height: 10px; background-color: red;"></div>
with 5.2 Ah PXC+	32	<div style="width: 32%; height: 10px; background-color: red;"></div>
with 4-6 Ah PXC+ (4 Ah mode)	22	<div style="width: 22%; height: 10px; background-color: red;"></div>
with 4-6 Ah PXC+ (6 Ah mode)	33	<div style="width: 33%; height: 10px; background-color: red;"></div>
best performance with min.	all packs	