



#### **Dirt Water Pump**

### **GE-DP 5220 LL ECO**

ltem No.: 4170780

Ident No.: 21030

Bar Code: 4006825598780

The 2in1 combined pump GE-DP 5220 LL ECO is a robust and reliable aid for the quick drainage of ponds, building pits or flooded cellars, and can be used for clear or waste water with up to 2 cm particle size. With its power consumption of just 520 Watt, this powerful submersible pump delivers up to 13,500 litres of water per hour and thereby convinces by its optimum energy efficiency. Quick adjustment of the required pump settings can be reached by means of its patented function- and suction level control. The extremely robust pump housing with high-quality mechanical seal (ceramic/rubber) resists even heavy drainage works reliably, and grants a long service life.

## **Features & Benefits**

- 2in1 combined pump clear and dirty water with one item
- Clear water: low level submersible up to 1mm residual water level
- Dirty water: up to 20 mm of particle size in coarse water
- Starting of pump from water level of 10 mm already possible
- Patented suction level control by easy rotational motion
- Infinitely height-adjustable float switch
- High-quality mech. seal (ceramic/rubber) for a long service life
- Ergonomic carrying handle with integrated lifting eye
- Easily reachable hose connection on the pump's topside
- Hose connection approx. 47.8 mm (G 1 1/2) AG
- Universal adapter for 25/32 mm hoses as well as 33.3 mm (G 1)
- Automatic mode for requested water level (float switch)
- Overload switch
- Housing made of impact-resistant plastic
- ECO-Power: higher delivery rate, lower power consumption

## **Technical Data**

-	Mains	supply
---	-------	--------

- Power
- Max. delivery capacity
- Max. delivery height
- Max. immersion depth
- Max. water temperature
- Max. size of foreign particles
- Hose connection
- Power cord

# Logistic Data

-	Product	weight
---	---------	--------

- Gross weight single packaging
- Dimensions single packaging
- Pieces per export carton
- Gross weight export carton
- Dimensions export carton
- Container quantity (20"/40"/40"HC)

5.49 kg
6.41 kg
240 x 240 x 380 mm
3 Pieces
19.85 kg
750 x 270 x 420 mm
885   1845   2214

47,8mm (G11/2 AG)

10 m | H05RN-F

230 V | 50 Hz

520 W

7 m 35 °C

20 mm

13500 L/h 7.5 m







