



# Einhell

## EXPERT PLUS



### Cordless Rotary Hammer

### HEROCCO KIT +5 (1x3,0Ah)

Item No.: 4513975

Ident No.: 21010

Bar Code: 4006825658286

The Einhell cordless rotary hammer Herocco delivers more power and provides longer operation thanks to the brushless motor. Drilling, hammer drilling or chiseling with or without lock make it a valued allrounder. It is a member of the Power X-Change family. The pneumatic impact mechanism makes effortless progress through concrete. Tools can be changed quickly thanks to the universal SDS-plus tool chuck with auto-slip-in function. The ergonomic grip area provides a firm soft grip hold. The LED light illuminates the work area. Complete with 3.0 Ah battery, PXC high-speed 3A charger, 3 drill bits (8, 10, 12 mm), pointed chisel, flat and bit adapter. For optimum operation it is recommended to use a 3.0 Ah battery or higher.

## Features & Benefits

- A member of the Power X-Change family
- Brushless motor - more power and prolonged operation
- 4 functions: Drilling/impact drilling/chiseling with and w/o lock
- Pneumatic impact mechanism for effortless drilling in concrete
- Universal SDS-plus chuck with semi-automatic function
- Speed electronics for fine adjustment on delicate jobs
- Low-vibration operations by vibration-cushioned main handle
- Ergonomic handle and additional handle with soft grip
- Infinitely adjustable drilling depth stop made of solid metal
- Incl. LED lamp to illuminate the work area
- Complete with 3.0 Ah battery, PXC high-speed 3A charger, 3 drill bits (8, 10, 12 mm), pointed chisel, flat chisel and bit adapter
- Recommendation for optimum results: 3.0 Ah battery & higher
- Supplied in transport and storage case E-Box



## Technical Data

- |                                 |                          |
|---------------------------------|--------------------------|
| - Accumulator                   | 18 V   3000 mAh   Li-Ion |
| - Number of accumulators        | 1 Pieces                 |
| - Charging time                 | 60 min                   |
| - Idle speed (gear 1)           | 0-1200 min <sup>-1</sup> |
| - Impact rate (gear 1)          | 0-5500 min <sup>-1</sup> |
| - Impact power                  | 2.2 J                    |
| - Max. torque hard              | 18 Nm                    |
| - Drilling capacity in concrete | 20 mm                    |

## Logistic Data

- |                                      |                    |
|--------------------------------------|--------------------|
| - Pieces per export carton           | 4 Pieces           |
| - Gross weight export carton         | 24.5 kg            |
| - Tool weight                        | 2.12 kg            |
| - Gross Weight                       | 5.83 kg            |
| - Dimensions single packaging        | 400 x 360 x 120 mm |
| - Dimensions export carton           | 505 x 415 x 375 mm |
| - Container quantity (20"/40"/40"HC) | 1248   2592   3024 |



## Available as special accessories



18V 30min Power X-Change  
Charger  
Item No.: 4512011  
Bar Code: 4006825587029  
Einhell Accessory



18V 5,2 Ah P-X-C Plus  
Battery  
Item No.: 4511437  
Bar Code: 4006825616606  
Einhell Accessory



Power-X-Boostcharger 6 A  
Charger  
Item No.: 4512064  
Bar Code: 4006825629019  
Einhell Accessory



Power-X-Twincharger 3 A  
Charger  
Item No.: 4512069  
Bar Code: 4006825629729  
Einhell Accessory



18V 2,0 Ah Power-X-Change  
Battery  
Item No.: 4511395  
Bar Code: 4006825610369  
Einhell Accessory



18V 4,0 Ah Power-X-Change  
Battery  
Item No.: 4511396  
Bar Code: 4006825610376  
Einhell Accessory



18V 3,0Ah PXC Starter Kit  
PXC-Starter-Kit  
Item No.: 4512041  
Bar Code: 4006825613698  
Einhell Accessory



18V 4,0Ah PXC Starter Kit  
PXC-Starter-Kit  
Item No.: 4512042  
Bar Code: 4006825613704  
Einhell Accessory

## -Running-Times

### screws (screw in 6x60 mm)

Usage	screwing	
Unit of measure	pieces	
with 1.5 Ah PXC	250	<div style="width: 25%; background-color: red;"></div>
with 2 Ah PXC	335	<div style="width: 33.5%; background-color: red;"></div>
with 2.5 Ah PXC	417	<div style="width: 41.7%; background-color: red;"></div>
with 2.6 Ah PXC+	430	<div style="width: 43%; background-color: red;"></div>
with 3 Ah PXC	500	<div style="width: 50%; background-color: red;"></div>
with 3.0 Ah PXC+	500	<div style="width: 50%; background-color: red;"></div>
with 4 Ah PXC	670	<div style="width: 67%; background-color: red;"></div>
with 5.2 Ah PXC+	870	<div style="width: 87%; background-color: red;"></div>
with 4-6 Ah PXC+ (4 Ah mode)	670	<div style="width: 67%; background-color: red;"></div>
with 4-6 Ah PXC+ (6 Ah mode)	100	<div style="width: 10%; background-color: red;"></div>
best performance with min.	3.0 Ah	
reason for best performance recommendation	current	

holes (6x50 mm in concrete)

Usage	drilling	
Unit of measure	pieces	
with 1.5 Ah PXC	65	
with 2 Ah PXC	87	
with 2.5 Ah PXC	108	
with 2.6 Ah PXC+	113	
with 3 Ah PXC	130	
with 3.0 Ah PXC+	130	
with 4 Ah PXC	174	
with 5.2 Ah PXC+	225	
with 4-6 Ah PXC+ (4 Ah mode)	174	
with 4-6 Ah PXC+ (6 Ah mode)	260	