







#### **TE-TS 36/210 Li-Solo**

Item No.: 4340450

Ident No.: 11019

Bar Code: 4006825647365

OWER X-CHANGE

The Einhell TE-TS 36/210 Li bench-type circular saw is an ideal, compact basic tool for anyone performing woodworking jobs, incl. for mobile use. The aluminium table is light and at the same time torsion-resistant. For wider workpieces the table has a pull-out width extension on the right-hand side. The height of the saw blade is infinitely adjustable and the blade can be tilted 45° to the left. The parallel stop ensures exact longitudinal cuts. The product is supplied with an angle stop for precise miter cuts from -60 to +60° degrees. Also included is a high-grade carbide saw blade, extra-thin for fine cuts and battery-saving operation. To minimize the amount of dirt, extractor connectors are provided on the housing and saw blade guard.

### Features & Benefits

- Member of the Power X-Change family, 2x18V batteries necessary
- Sturdy aluminium table, light and perfect sliding properties
- Pull-out table width extension on right side for wider workpieces
- Small and compact, ideal for limited space or mobile use
- The soft start function protects both the motor and the gear unit
- Ultra-sturdy parallel stop for exact longitudinal cuts
- Incl. angle stop for precise miter cuts of -60 to +60°
- High-grade carbide-tipped saw blade, developed for cordless saws
- Infinitely height adjustable saw blade for extra safety
- Saw blade can be tilted continuously up to 45° for miter cuts
- Extractor connection on housing and saw blade guard for less mess
- Holders for stowing away all the attachments on the equipment
- Recommendation for best results: PXC 2.5 Ah battery or higher



## **Technical Data**

- No-load speed 3800 min^-1 - Saw Blade Ø210 x Ø30 mm - Number of saw teeth 40 Pieces - Swiveling range of saw blade 45° - Max. cutting height at 90° 70 mm - Max. cutting height at 45° 45 mm

- Size of working table 480 x 467 mm - Size of extension table right 480 x 70 mm - Extension table telescopic 370 mm













# **Logistic Data**

- Product weight (kg) 13.15 - Gross weight (kg) 17.76

- Dimensions single packaging 660 x 580 x 330 mm

- Pieces per export carton 1 Pieces - Gross weight of export carton 17.76 kg

660 x 580 x 330 mm - Dimensions export carton - Container quantities (20"/40"/40"HC) 224 | 504 | 571







### Available as special accessories



Power X-Boostcharger 6A Charger Item No.: 4512064 Bar Code: 4006825629019 Einhell Accessory



18V 3,0Ah Power X-Change Plus Battery Item No.: 4511501 Bar Code: 4006825644197 Einhell Accessory



18V 4-6Ah Multi-Ah PXC Plus Battery Item No.: 4511502 Bar Code: 4006825644210 Einhell Accessory



18V 2,5Ah PXC Starter Kit PXC-Starter-Kit Item No.: 4512097 Bar Code: 4006825646962 Einhell Accessory



18V 2,0Ah Power X-Change Battery Item No.: 4511395 Bar Code: 4006825610369 Einhell Accessory



18V 4,0Ah Power X-Change Battery Item No.: 4511396 Bar Code: 4006825610376 Einhell Accessory



18V 3,0Ah PXC Starter Kit PXC-Starter-Kit Item No.: 4512041 Bar Code: 4006825613698 Einhell Accessory



18V 4,0Ah PXC Starter Kit TP PXC-Starter-Kit Item No.: 4512042 Bar Code: 4006825613704 Einhell Accessory



Extractor Adapter Set Stationary Accessory Item No.: 4310630 Bar Code: 4006825587715 Einhell Grey



18V 5,2Ah Power X-Change Plus Battery Item No.: 4511437 Bar Code: 4006825616606 Einhell Accessory

TCT Thin saw-blade 210x30 T40



TCT Thin saw-blade 210x30 T40 Stationary Saw Accessory Item No.: 49587852 Bar Code: 4009315878522 KWB by Einhell



Stationary Saw Accessory Item No.: 49587862 Bar Code: 4009315878621 KWB by Einhell 18V 3,0 Ah Power-X-Change Battery Item No.: 4511341

Bar Code: 4006825590593

Einhell Accessory



Power X-Twincharger 3A Charger Item No.: 4512069 Bar Code: 4006825629729 Einhell Accessory

## **Battery-Running-Times**

	A CONTRACTOR OF THE CONTRACTOR	
One Battery for All	sawing <sup>1</sup>	
	(m)	
1.5 Ah	45	
2.0 Ah	60	
2.5 Ah	71	
3.0 Ah	92	
4.0 Ah	122	
5.2 Ah	160	
6.0 Ah	184	

For best performance select a battery with at least 2.5 Ah

Test setup:

1) chipboard 19 mm