



Einhell

CLASSIC



Cordless Multifunctional Tool

TC-MG 18 Li-Solo

Item No.: 4465170

Ident No.: 21020

Bar Code: 4006825628593

The cordless multifunctional Einhell TC-MG 18 Li - Solo tool is a high-quality helper for extension, renovation and restoration jobs and is a member of the PXC family. The magnetic tool fixation with 12 adjustable settings enables the user to change accessories quickly and comfortable. The speed electronics allows the tool to be adapted to the particular material/application. The oscillation decoupled battery uptake with vibration reduction and the soft grip ensure comfortable operation. It comes with a triangular sanding plate, 9 sheets of abrasive paper (3*P60/3*P80/3*P120), scraper, plunge-cut saw blade for wood & plastic (HCS) as well as a segment saw blade additionally for soft metal (HSS). Supplied without battery and charger.

Features & Benefits

- Member of the Power X-Change family
- Comfortable accessory change thanks to magnetic tool fixation
- Speed electronics for material and application suitable working
- Oscillation decoupled battery uptake for reduction of vibration
- Safe and pleasant working thanks to soft grip
- 12-pin-tool fixation for flexible positioning of equipment
- Incl. triangular grinding/sanding plate
- Incl. 9x grinding/sanding paper (3*P60/3*P80/3*P120)
- Incl. scraper
- Incl. plunge-cut saw blade for wood and plastic (HCS)
- Incl. segment saw blade for wood, plastic and soft metal (HSS)
- Supplied without battery and charger (available separately)



Technical Data

- | | |
|------------------------|---------------------------------|
| - Oscillating speed | 22000-40000 min ⁻¹ |
| - No load speed | 11000 - 20000 min ⁻¹ |
| - Angle of oscillation | 3.2 ° |
| - Sandpaper size | 93 x 93 x 93 mm |



MAGNETIC TOOL FIXATION



REDUCED VIBRATION



SPEED ELECTRONICS

Logistic Data

- | | |
|--------------------------------------|----------------------|
| - Product weight | 0.88 |
| - Gross weight single packaging | 1.27 kg |
| - Dimensions single packaging | 77 x 167 x 259 mm |
| - Pieces per export carton | 10 Pieces |
| - Gross weight export carton | 14.3 kg |
| - Dimensions export carton | 535 x 405 x 190 mm |
| - Container quantity (20"/40"/40"HC) | 6620 13480 14400 |




SOFT GRIP



INCL.



18 V



MAGNETIC TOOL FIXATION



REDUCED VIBRATION

Available as special accessories

	Dust Adapter TC-MG 18 Li Multifunctional Tool Accessory Item No.: 4465171 Bar Code: 4006825628609 No Name		Power X-Boostcharger 6A Charger Item No.: 4512064 Bar Code: 4006825629019 Einhell Accessory
	2x 3,0Ah & Twincharger Kit PXC-Starter-Kit Item No.: 4512083 Bar Code: 4006825638509 Einhell Accessory		18V 4-6Ah Multi-Ah PXC Plus Battery Item No.: 4511502 Bar Code: 4006825644210 Einhell Accessory
	18V 3,0Ah Power X-Change Plus Battery Item No.: 4511501 Bar Code: 4006825644197 Einhell Accessory		18V 2,5Ah PXC Starter Kit PXC-Starter-Kit Item No.: 4512097 Bar Code: 4006825646962 Einhell Accessory
	18V 2,0Ah Power X-Change Battery Item No.: 4511395 Bar Code: 4006825610369 Einhell Accessory		18V 4,0Ah Power X-Change Battery Item No.: 4511396 Bar Code: 4006825610376 Einhell Accessory
	18V 4,0Ah PXC Starter Kit 1 PXC-Starter-Kit Item No.: 4512042 Bar Code: 4006825613704 Einhell Accessory		18V 2,5Ah Power X-Change Battery Item No.: 4511516 Bar Code: 4006825650518 Einhell Accessory
	Power X-Fastcharger 4A Charger Item No.: 4512103 Bar Code: 4006825650228 Einhell Accessory		18V 5,2Ah Power X-Change Plus Battery Item No.: 4511437 Bar Code: 4006825616606 Einhell Accessory
	Power X-Twincharger 3A Charger Item No.: 4512069 Bar Code: 4006825629729 Einhell Accessory		2x18V 4,0Ah PXC-Twinpack CB 1 Battery Item No.: 4511489 Bar Code: 4006825638578 Einhell Accessory

Battery-Running-Times

One Battery for All	 sawing ¹ (min.)	 sanding ² (min.)	 cutting ³ (pieces)	 cutting ⁴ (pieces)
1.5 Ah	23	23	540	100
2.0 Ah	30	30	720	134
2.5 Ah	38	38	900	166
3.0 Ah	45	45	1080	200
4.0 Ah	60	60	1440	268
5.2 Ah	78	78	1880	340
6.0 Ah	90	90	2160	400

Test setup:

- 1) -
- 2) -
- 3) plastic - round plastic Ø 10 mm
- 4) metal - round steel Ø 6 mm