





PXC-Starter-Kit

2x 4,0Ah & Twincharger Kit

Item No.: 4512112

Ident No.: 21021

Bar Code: 4006825655766

The Einhell 18V 2x 4.0Ah PXC Starter Kit is the ideal basis for starting or expanding the Power X-Change range in your home. A single rechargeable battery and a single charger for all tools not only saves significant costs of buying, universal use also helps protect the environment and provides flexibility. For high Power, long + sustained working time and to use 36V (2x18V) devices, two Batteries are included. The ABS process-controlled active battery management system ensures maximum safety, optimum tool performance, maximum operating time and a maximum service life. The high-speed charging technology means short charging times, and for optimum charging and maximum safety the battery is permanently monitored by a charging management system

OWER X-CHANGE

Features & Benefits

- Universal usability for all Power X-Change rechargeable devices:
- Saving money, protecting the environment, and flexibility
- Longer working time and more power with 2x 18V batteries (= 36V)
- Battery features:
- The ABS process-controlled battery management system stands for
- max. safety, optimum performance, operating time + lifetime
- Freedom of cordless operation: No tangled cables and free working
- High-quality Li-Ion cells means no memory effect,
- low self-discharge and high, constant power
- Current charge level indicated by 3-stage LED display
- Impact protection and good grip thanks to rubber-coated housing
- Trough handle for easy removal
- Housing protected against dust, corrosion and mechanical damage
- Suitable for TWIN-PACK use in power demanding 36V applications
- Charger features:
- Parallel Charging of 2x 18V batteries saves space,
- provides fast + high availability and continuous working
- Quick-charge technology ensures short charging times
- Permanent battery monitoring for optimum charging
- Refresh mode allows deeply discharged batteries to be reactivated
- Maximum safety due to intelligent charge management
- Current information on 6-stage status LED display
- Integrated suspension eyelets for user-friendly wall-mounting







Technical Data

220-240 V | 50-60 Hz - Mains supply charger

- Voltage output charger 18 V - Charging time 75min 18 V - Voltage 4000 mAh - Battery capacity 900 W - Max. power - Amount of batteries 2 Pieces

Logistic Data

- Product weight (kg) 0.767- Gross weight (kg) 2.29

- Dimensions single packaging 265 x 85 x 301 mm
- Pieces per export carton 6 Pieces

Gross weight of export carton
 Dimensions export carton
 15.7 kg
 540 x 300 x 277 mm

- Container quantity (20"/40"/40"HC) 3474 | 7482