



Einhell

CAR CLASSIC

Battery Charger

CC-BC 30/1

Item No.: 1078121

Ident No.: 21020

Bar Code: 4006825612691

The CC-BC 30/1 battery charger is a powerful and robust charger for workshops with switchable charging voltage of 6V/12V/24V and starting aid equipment. Therefore, it is optimally suitable for workshops, agricultural purposes and payload traffic. The charging rate is adjustable at 6 steps, and the starting aid equipment (100A/5s) can easily be operated by a jump starting switch on the device. The current charging rate, as well as the charging voltage, can be read from the two largely dimensioned display instruments, and the charging procedure can be supervised. The totally insulated terminal clamps grant an optimal contact to the battery terminals. Additionally, it is equipped with a 2-fold reverse polarity- and overload protection.

Features & Benefits

- Construction protection class I
- Overload- and false poling- and short-circuit protection
- Sheet steel housing
- Carrying handle
- 2in1: Charging and jump starting with one item
- Charging voltage switch
- Charging rate switch
- Voltmeter and ammeter
- Mains cable with safety plug
- Charging cable with isolated pole clamps



Technical Data

- Mains supply 230 V | 50 Hz
- Jump start yes
- Charging voltage 6 V/ 12V/ 24V
- Suitable for batteries (from min. Ah to max. Ah): 3-400 Ah
- Boost engine output (Ampere for seconds) 100 A - 5 sec
- Charging current Min. (arith./eff.) - Max. 0,7 / 0,9 - 21 / 30 A (arith./eff.) on 6 V d.c.
- Charging current Min. (arith./eff.) - Max. 1,0 / 1,6 - 20 / 30 A (arith./eff.) on 12 V d.c.
- Charging current Min. (arith./eff.) - Max. 1,8 / 3,0 - 14 / 20 A (arith./eff.) on 24 V d.c.



Logistic Data

- Product weight 11.88 kg
- Gross weight single packaging 12.95 kg
- Dimensions single packaging 424 x 318 x 220 mm
- Pieces per export carton 2 Pieces
- Gross weight export carton 26.5 kg
- Dimensions export carton 645 x 435 x 245 mm
- Container quantity (20"/40"/40"HC) 828 | 1656

