





Power Generator (Petrol)

TC-PG 25/1/E5

Item No.: 4152600

Ident No.: 21021

Bar Code: 4006825657319

The Einhell generator (petrol) TC-PG 25/1/E5 generates a continuous output of 2,100 W and a max. output of 2,400 W thanks to its powerful, robust and clean 4-stroke drive motor. Thanks to compliance with emissions 5 regulations, the air-cooled four-stroke petrol motor is low-emission in operation. For transferring electricity to terminal devices it has two 230 V socket-outlets including a voltmeter which shows the voltage. The AVR function (automatic voltage control system) ensures stable output power. The large 15 liter tank has a practical fill level indicator for continuous operation. For long-lasting use the equipment has an overload switch and low oil cut-out. The generator is started by an easy to use cable pull.

Features & Benefits

- Powerful, robust and clean 4-stroke drive motor
- Low-emission motor due to compliance with emission 5 regulations
- Two 230 V socket-outlets incl. voltmeter for showing the voltage
- Large 15-liter tank with level indicator for continuous operation
- Overload switch and low oil cut-out for long-lasting use
- AVR function for stable output power
- Easy to use cable pull for starting

Technical Data

- Type of generator Synchronous - Frequency 50 Hz - Continous power (S1) at 230 V 2100 W - Max. power | time (230 V) 2400 W

- Power (S2 | S2time) at 230 V 2300 W | 5 min - Nominal current at 230 V 9.1 A

- 230 V socket 2 Pieces - Engine four-stroke, air cooled 1 Pieces

- Number of cylinders - Engine displacement 212 cm³ - Engine speed 3000 min^-1 - Max. engine power 4.15 kW

- Fuel Petrol (unleaded) / E10 - Capacity of fuel tank 15 I

- Running time with 2/3 load 12.5 h - Sound power level LWA 96 dB (A)

Logistic Data

- Product weight 38 kg - Gross weight single packaging 39.86 kg

- Dimensions single packaging 600 x 450 x 445 mm - Pieces per export carton 1 Pieces

- Gross weight export carton 39.86 kg

- Dimensions export carton 610 x 455 x 460 mm

- Container quantity (20"/40"/40"HC) 225 | 475















STROKE **PETROL ENGINE**

HIGH **CAPACITY TANK** 15 I