



Einhell

CLASSIC

Impact Wrench (Pneumatic)

TC-PW 610

Item No.: 4138960

Ident No.: 11018

Bar Code: 4006825639971

The Einhell TC-PW 610 pneumatic impact wrench is a powerful and robust tool with maximum torque of 610 Nm. It is also equal to every challenge in the home, workshop and garage thanks to its high power. The non-slip, rubberized handle ensures that it is safe to work with. Featuring counter-clockwise (one-step) and clockwise (three-step) operation, the pneumatic impact wrench can be used for a whole range of assignments. Top performance is offered using a hose with an inner diameter of 9 mm or over. The product comes complete with 10 drill sockets in sizes 8/10/11/13/17/19/21/22/24/27 mm and one small oil bottle, one nipple and one 125 mm extension. Supplied in a practical transport and storage case.

Features & Benefits

- Powerful impact wrench with max. torque of 610 Nm
- Also suitable for challenging tasks thanks to high power
- Non-slip rubberized handle for safety during use
- Counter-clockwise (one-step) and clockwise operation (three-step)
- Top performance with a hose inner diameter of 9 mm or more
- With 10 drill sockets in sizes 8/10/11/13/17/19/21/22/24/27 mm
- Incl. 1 small oil bottle and 1 nipple
- Incl. 1 x 125 mm extension
- Supplied in a practical transport and storage case



Technical Data

- | | |
|---------------------------|------------------------|
| - Max. torque (step 1) | 220 Nm |
| - Max. torque (step 2) | 340 Nm |
| - Max. torque (step 3) | 610 Nm |
| - Operating pressure max. | 6.3 bar |
| - No-load speed | 7000 min ⁻¹ |
| - Air consumption | 198 L/min |
| - Square drive | 0.5 Inch |



Logistic Data

- | | |
|--------------------------------------|--------------------|
| - Product weight | 2.1 kg |
| - Gross weight single packaging | 4.2 kg |
| - Dimensions single packaging | 346 x 83 x 255 mm |
| - Pieces per export carton | 4 Pieces |
| - Gross weight export carton | 18 kg |
| - Dimensions export carton | 540 x 365 x 200 mm |
| - Container quantity (20"/40"/40"HC) | 2800 5500 5500 |

