







GE-UB 18/250 Li E-Solo

Item No.: 3433542

Ident No.: 21010

Bar Code: 4006825659405

With the Einhell cordless universal blower GE-UB 18/250 Li E-Solo there is order in the house and garden. Being a member of the Power X-Change family, 1x18 V battery is required. The multi-part blowing pipe can be used for various applications; for example, as a leaf blower with a long blowing pipe, as a workshop blower with a medium or as a grill ignition aid with a short precision blowing pipe. The electronic speed control ensures that the required adjustment is made. The LED display shows the speed. The softgrip ensures good grip and fatigue-free working. The integrated wall mount allows for easy storage. For optimal results, a 2.5 Ah battery or higher is recommended. Delivery does not include battery or charger (sold separately).

OWER X-CHANGE

Features & Benefits

- Member of the Power X-Change family, 1x18V batteries necessary
- 3-parts tube for different applications in house & garden
- Useable as leaf-blower with long tube
- Useable as workshop-blower with middle tube
- Useable as barbecue firing aid with short, precision tube
- Electronic speed control for adjustments to diff. applications
- LED indication shows the set speed at one glance
- Soft grip for good grip and fatigue-free work
- Integrated wall holder for easy storage
- Recommended for perfect results: 2.5Ah battery and bigger
- Supplied without battery and charger (available separately)



Technical Data

- No-load speed (idle speed) 15000 min^-1 - Blow velocity 250 km/h - Max. air volume 120 m³/h



- Product weight 1.1 kg - Gross weight single packaging 2.01 kg

- Dimensions single packaging 405 x 175 x 230 mm 8 Pieces - Pieces per export carton

- Gross weight export carton 17 kg

720 x 421 x 480 mm - Dimensions export carton - Container quantity (20"/40"/40"HC) 1544 | 3216 | 3664















BEST WITH



Available as special accessories



2x 3,0Ah & Twincharger Kit PXC-Starter-Kit Item No.: 4512083 Bar Code: 4006825638509





18V 2,5Ah PXC Starter Kit PXC-Starter-Kit Item No.: 4512097 Bar Code: 4006825646962 Einhell Accessory



18V 4,0Ah Power X-Change 1 Battery Item No.: 4511396 Bar Code: 4006825610376 Einhell Accessory



2x2 Power X-Quattrocharger 4A Charger Item No.: 4512102 Bar Code: 4006825649536 Einhell Accessory



Power X-Fastcharger 4A Charger Item No.: 4512103 Bar Code: 4006825650228 Einhell Accessory



Power X-Twincharger 3A Charger Item No.: 4512069 Bar Code: 4006825629729

Einhell Accessory



2x 4,0Ah & Twincharger Kit 1 PXC-Starter-Kit Item No.: 4512112 Bar Code: 4006825655766 Einhell Accessory



2x 18V 5,2Ah PXC-Twinpack Battery Item No.: 4511526 Bar Code: 4006825656695 Einhell Accessory



PXC Akku-Wandhalterung Case Item No.: 4514155 Bar Code: 4006825658774 Einhell Accessory



Power X-Boostcharger 6A Charger Item No.: 4512064 Bar Code: 4006825629019 Einhell Accessory



18V 5-8Ah Multi-Ah PXC Plus Battery Item No.: 4511600 Bar Code: 4006825665055 Einhell Accessory



18V 4-6Ah Multi-Ah PXC Plus Battery Item No.: 4511502 Bar Code: 4006825644210 Einhell Accessory



18V 2,0Ah Power X-Change Battery Item No.: 4511395 Bar Code: 4006825610369 Einhell Accessory



18V 4,0Ah PXC Starter Kit 1 PXC-Starter-Kit Item No.: 4512042 Bar Code: 4006825613704 Einhell Accessory



18V 2,5Ah Power X-Change Battery Item No.: 4511516 Bar Code: 4006825650518 Einhell Accessory



18V 5,2Ah Power X-Change Plus Battery Item No.: 4511437 Bar Code: 4006825616606 Einhell Accessory



Power X-Car Charger 3A Charger Item No.: 4512113 Bar Code: 4006825655377 Einhell Accessory



2x 18V 2,5Ah PXC-Twinpack CB Battery Item No.: 4511524 Bar Code: 4006825656206 Einhell Accessory



5,2Ah & 4A Fastcharger PXC-Starter-Kit Item No.: 4512114 Bar Code: 4006825656787 Einhell Accessory



2x18V 4,0Ah PXC-Twinpack CB 1 Battery Item No.: 4511489 Bar Code: 4006825638578 Einhell Accessory



18V 3,0Ah Power X-Change Plus Battery Item No.: 4511501 Bar Code: 4006825644197 Einhell Accessory

Battery-Running-Times

| | | |
|---------------------|----------------------|----------------------|
| One Battery for All | blowing ¹ | blowing ² |
| | (min.) | (min.) |
| 1.5 Ah | 7 | 48 |
| 2.0 Ah | 10 | 65 |
| 2.5 Ah | 12 | 80 |
| 3.0 Ah | 14 | 96 |
| 4.0 Ah | 20 | 130 |
| 5.2 Ah | 24 | 166 |
| 6.0 Ah | 28 | 192 |
| 8.0 Ah | 40 | 260 |

For best performance select a battery with at least 2.5 Ah

Test setup

1) Max. electronic speed

2) Min. electronic speed